



## Canon RF 70-200mm F2.8L IS USM Z MILC Telephoto zoom lens Black, White

**Brand :** Canon

**Product code:** 6594C005

**Product name :** RF 70-200mm F2.8L IS USM Z

RF 70-200mm F2.8L IS USM Z Lens, White

Canon RF 70-200mm F2.8L IS USM Z MILC Telephoto zoom lens Black, White:

Smooth, agile and practical, this powerful zoom lens is ideal for professional photographers and videographers looking for added flexibility and reach. The RF 70-200mm F2.8L IS USM Z joins the RF 24-105mm F2.8L IS USM Z in Canon's line-up of professional hybrid camera lenses as its standard telephoto zoom counterpart, offering a focal length range of 70-200mm along with professional filmmaking features such as a constant f/2.8 aperture, a built-in Optical Image Stabiliser<sup>1</sup> and dedicated iris ring. With the option to attach RF Extenders for extended reach, the RF 70-200mm F2.8L IS USM Z is a versatile and adaptable telephoto lens for professional video and photo.



| Lens system                                   |                                                                       | Performance                                  |                                                       |
|-----------------------------------------------|-----------------------------------------------------------------------|----------------------------------------------|-------------------------------------------------------|
| Component for *                               | MILC                                                                  | Maximum magnification                        | 0.3x                                                  |
| Lens type *                                   | Telephoto zoom lens                                                   | Ultrasonic motor (USM)                       | ✓                                                     |
| Lens structure (elements/groups) *            | 18/15                                                                 | Circular aperture                            | ✓                                                     |
| Lens viewing angle, horizontal                | 29 - 10°                                                              | Lens coating features                        | Air Sphere Coating (ASC), Super Spectra Coating (SSC) |
| Lens viewing angle, vertical                  | 19° 30' - 7                                                           | Number of Ultra-low Dispersion (UD) elements | 1                                                     |
| Lens viewing angle, diagonal                  | 34 - 12°                                                              | Lens hood                                    | ✓                                                     |
| Focal length range                            | 70 - 200 mm                                                           | Lens hood type                               | Removable lens hood                                   |
| Minimum aperture number *                     | 22                                                                    | Lens hood model                              | ET-88C                                                |
| Number of diaphragm blades                    | 11                                                                    | <b>Design</b>                                |                                                       |
| Closest focusing distance *                   | 0.49 m                                                                | Product colour                               | Black, White                                          |
| Maximum aperture number *                     | 2.8                                                                   | Mounting type                                | Bayonet                                               |
| Number of aspheric elements                   | 3                                                                     | Dustproof                                    | ✓                                                     |
| Zoom capability *                             | ✓                                                                     | Moisture-resistant                           | ✓                                                     |
| Image sensor format                           | Full frame                                                            | <b>Logistics data</b>                        |                                                       |
| Lens mount interface *                        | Canon RF                                                              | Layers per pallet                            | 3 pc(s)                                               |
| Teleconverter/Extender compatible             | ✓                                                                     | <b>Weight &amp; dimensions</b>               |                                                       |
| Control ring                                  | ✓                                                                     | Length                                       | 199 mm                                                |
| Image stabilizer                              | ✓                                                                     | Weight                                       | 1.11 kg                                               |
| Image stabilizer type                         | In-Body Image Stabilization (IBIS), Optical Image Stabilization (OIS) | Diameter *                                   | 8.85 cm                                               |
| Image stabilizer number of stops (OIS)        | 5.5                                                                   | Filter size *                                | 82 mm                                                 |
| Image stabilizer number of stops (IBIS x OIS) | 7.5                                                                   | <b>Packaging data</b>                        |                                                       |
| <b>Performance</b>                            |                                                                       | Package width                                | 184 mm                                                |
| Auto focus                                    | ✓                                                                     | Package depth                                | 184 mm                                                |
| Manual focus                                  | ✓                                                                     | Package height                               | 332 mm                                                |
| AF actuator                                   | Dual Nano USM                                                         | Package weight                               | 2.11 kg                                               |
| Camera brands compatibility *                 | Canon                                                                 |                                              |                                                       |

| Packaging content      |         |
|------------------------|---------|
| Lens cap included      | ✓       |
| Lens cap model         | E-82 II |
| Rear lens cap included | ✓       |
| Rear lens cap model    | RF      |



4549292240597

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.