

TP-Link INSIGHT S445 Turret IP security camera Outdoor 2688 x 1520 pixels Ceiling



Brand : TP-Link

Product code: INSIGHT S445(4MM)

Product name : INSIGHT S445

- 4MP Super-High Definition and 24h Full-Color
- People & Vehicle Analytics
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Active Defense and Two-Way Audio
- IP67 Waterproof
- H.265+ Compression Technology

VIGI 4MP Full-Color Turret Network Camera, 1/2.7", 1/3 to 1/10000 s, F1.6, 2688 x 1520, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC $\pm$ 5%, Max. 11 W, 5.5 mm Coaxial Power Plug, PoE: 802.3af/at, class 0, Max. 12 W, IP67, 111 x 111 x 83.7 mm, 0.48 kg, White

TP-Link INSIGHT S445. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Turret. Lens viewing angle, horizontal: 80.4°, Lens viewing angle, vertical: 41.8°, Lens viewing angle, diagonal: 98.7°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Sensor type (panoramic camera): CMOS, Signal-to-Noise Ratio (SNR) (panoramic camera): 52 dB

Performance		Video	
Type *	IP security camera	Digital Wide Dynamic Range (DWDR)	✓
Placement supported *	Outdoor	Audio	
Connectivity technology *	Wired	Built-in speaker(s)	✓
Maximum operating distance	80 m	Audio system	2-way
Wide Dynamic Range (WDR)	✓	Audio input channels	1.0 channels
Day/night mode	✓	Audio output channels	1.0 channels
Infrared (IR) cut-off filter	✓	Audio formats supported	G.711 A-law
Remote viewing	✓	Sample rate	8 kHz
Dynamic range	120 dB	Built-in microphone	✓
Design		Number of microphones	1
Form factor *	Turret	Bit rate range	0 - 64 Kbit/s
Mounting type *	Ceiling	Network	
Product colour *	White	Ethernet LAN *	✓
Housing material	Metal	Networking standards	IEEE 802.3af, IEEE 802.3at
Protection features	Waterproof	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
International Protection (IP) code	IP67	Wi-Fi *	✗
Weatherproof	✓	Bluetooth *	✗
Camera		Live view	✓
Minimum illumination	0 lx	Storage	
Lens viewing angle, horizontal	80.4°	Compatible memory cards	MicroSD (TransFlash)
Lens viewing angle, vertical	41.8°	Maximum memory card size	512 GB
Lens viewing angle, diagonal	98.7°	Ports & interfaces	
Tilt angle range	0 - 90°	Ethernet LAN (RJ-45) ports	1
Camera shutter speed	1/3 to 1/10000	Security	
Image sensor		Built-in siren	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")		
Progressive scan	✓		
Sensor type *	CMOS		


Panoramic camera		Security	
Sensor type (panoramic camera)	CMOS	Password protection	✓
Signal-to-Noise Ratio (SNR) (panoramic camera)	52 dB	Video motion detection	✓
Digital Wide Dynamic Range (DWDR) (panoramic camera)	✓	IP address filtering	✓
Lens system		HTTPS encryption	✓
		Alert notification type	Push notification
		Motion sensor	✓
		Mirror	✓
		Digest authentication	✓
		Management features	
		Web browser	✓
		Cloud-managed *	✓
Night vision		Reset button	✓
		Power	
Night vision *	✓	Power source type *	DC, PoE
LED type	IR/White	Power consumption (max)	11 W
Video		Power consumption (Power over Ethernet (PoE))	12 W
		DC output voltage	12
		Operational conditions	
		Operating temperature (T-T)	-30 - 60 °C
		Storage temperature (T-T)	-40 - 60 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Weight & dimensions	
Maximum resolution *	2688 x 1520 pixels	Width	111 mm
Total megapixels *	4 MP	Height	83.7 mm
Video compression formats	H.264, H.264+, H.265, H.265+ 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520	Length	111 mm
Supported graphics resolutions		Weight	480 g
Video recording	✓	Packaging data	
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Package type	Box
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Packaging content	
Bit rate	Main Stream: 256 Kbps to 6 Mbps, Sub-Stream: 64 Kbps to 512 Kbps	Number of cameras *	1
Back Light Compensation (BLC)	✓	Mounting kit	✓
Highlight Compensation (HLC)	✓	Screws included	✓
		Drilling template included	✓
		Manual	✓




0810142823999



810142823999



1210002606332



8885020628227

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.