



Cudy GS1010PS2 network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Brand : Cudy

Product code: GS1010PS2

Product name : GS1010PS2

- 8× GbE with 802.3at/af Mode A PoE
- 2× Uplink GbE + 2× Uplink SFP
- 120W Power Supply
- Extend On/Off, VLAN On/Off
- Watchdog On/Off
- PoE Max, PoE per Port LED
- 256×170×44 mm (10.08×6.69×1.73")

8-Port Gigabit PoE+ Switch with 2 GbE and 2 Gigabit SFP

Cudy GS1010PS2. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 2048 entries, Switching capacity: 24 Gbit/s. Networking standards: IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Power over Ethernet (PoE). Rack mounting

Management features		Power	
Switch type *	Unmanaged	AC input voltage	100 - 240 V
Ports & interfaces		AC input frequency	50/60 Hz
Basic switching RJ-45 Ethernet ports quantity *	10	Power consumption (max)	120 W
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
SFP module slots quantity	2	Power over Ethernet (PoE) *	✓
Network		Power over Ethernet (PoE) ports quantity	8
Networking standards *	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) power per port	30 W
10G support *	✗	Total Power over Ethernet (PoE) budget	120 W
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X	Operational conditions	
Cable types supported	Cat3, Cat5, Cat5e	Operating temperature (T-T)	0 - 40 °C
Flow control support	✓	Storage temperature (T-T)	-40 - 70 °C
Data transmission		Operating relative humidity (H-H)	10 - 90%
Switching capacity *	24 Gbit/s	Storage relative humidity (H-H)	10 - 95%
Forwarding rate	17.856 Mpps	Weight & dimensions	
MAC address table *	2048 entries	Width	220 mm
Store-and-forward	✓	Depth	161 mm
Jumbo frames support	✓	Height	44 mm
Jumbo frames	2000	Weight	934 g
Packet buffer memory	0.448 MB	Packaging content	
Design		Cables included	AC
Rack mounting *	✓	Quick start guide	✓
Product colour	Black	Packaging data	
Housing material	Metal	Package width	315 mm
LED indicators	Link, Power	Package depth	215 mm
Power		Package height	85 mm
Power source *	AC	Package weight	1.3 kg
Power supply included *	✓		



6971690793319

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.