



Cudy GS1026PS2 network switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Brand : Cudy

Product code: GS1026PS2

Product name : GS1026PS2

- 24x GbE with 802.3at/af PoE
 - 2x Uplink GbE + 2x Uplink SFP
 - 300W Power Supply
 - Extend On/Off, VLAN On/Off
 - Watchdog On/Off
 - PoE Max, PoE per Port LED
 - Smart Fan Cooling
 - Desktop, Rack-Mount
 - 440x180x44 mm (17.32x7.09x1.73")
- 24-GbE PoE Switch with 2 Uplink GbE and 2 Uplink SFP

Cudy GS1026PS2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 26. MAC address table: 8192 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting

Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	26	Power consumption (max)	300 W
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
SFP module slots quantity	2	Power over Ethernet (PoE) *	✓
Power connector	AC-in jack	Power over Ethernet plus (PoE+) ports quantity	24
Network		Power over Ethernet (PoE) power per port	30 W
Networking standards *	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Total Power over Ethernet (PoE) budget	300 W
10G support *	✗	Operational conditions	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X	Operating temperature (T-T)	0 - 40 °C
Cable types supported	Cat3, Cat5, Cat5e	Storage temperature (T-T)	-40 - 70 °C
Flow control support	✓	Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	10 - 95%
Data transmission		Weight & dimensions	
Switching capacity *	56 Gbit/s	Width	320 mm
Forwarding rate	41.664 Mpps	Depth	207 mm
MAC address table *	8192 entries	Height	44 mm
Store-and-forward	✓	Weight	1.99 kg
Packet buffer memory	0.375 MB	Packaging content	
Design		Cables included	AC
Rack mounting *	✓	Quick start guide	✓
Product colour	Black	Rack mount kit	✓
Housing material	Metal	Packaging data	
LED indicators	Link, PoE, Power	Package width	370 mm
Power		Package depth	290 mm
Power source *	AC	Package height	85 mm
Power supply included *	✓	Package weight	2.53 kg
AC input voltage	100 - 240 V		
AC input frequency	50/60 Hz		



6971690793333

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.