



## Lindy 39365 сетевой удлиннитель Сетевой передатчик и приемник Черный

Производитель : Lindy

Код товара: 39365

Модель : 39365

Lindy 39365. Тип: Сетевой передатчик и приемник, Максимальное расстояние передачи: 100 m, Скорость передачи данных: 480 Мбит/с. Материал контакта: Фосфористая бронза, Покрытие контактов разъема: Золото, Материал разъема: Золото. Цвет товара: Черный, Материал корпуса: Металл, Сертификация: CE, UKCA, FCC, RoHS & REACH, CP65. Выходное напряжение: 24 V, Ток на выходе: 3,75 A, Power note: 5.5/2.1mm DC. Ширина: 180 mm, Глубина: 95 mm, Высота: 23 mm



| Производительность                                 |                               | Энергопитание                                     |                   |
|----------------------------------------------------|-------------------------------|---------------------------------------------------|-------------------|
| Тип *                                              | Сетевой передатчик и приемник | Ток на выходе                                     | 3,75 A            |
| Максимальное расстояние передачи *                 | 100 m                         | Питание по Ethernet (PoE)                         | ✓                 |
| Скорость передачи данных                           | 480 Мбит/с                    | Power note                                        | 5.5/2.1mm DC      |
| Поддерживаемые типы кабеля                         | Cat6a                         | Типы встроенных разъемов электропитания           | AU, EU, UK, US    |
| Чипсет (передатчик)                                | VS6320                        | <b>Условия эксплуатации</b>                       |                   |
| Plug & Play                                        | ✓                             | Диапазон температур при эксплуатации              | 0 - 40 °C         |
| Порты и интерфейсы                                 |                               | Диапазон температур при хранении                  | -20 - 60 °C       |
| Количество портов Ethernet LAN (RJ-45)             | 2                             | Диапазон относительной влажности при эксплуатации | 10 - 90%          |
| Количество портов RJ-45 (передатчик)               | 1                             | Диапазон относительной влажности при хранении     | 10 - 90%          |
| Количество портов RJ-45 (приемник)                 | 1                             | <b>Вес и размеры</b>                              |                   |
| USB Type-C ports quantity (transmitter)            | 4                             | Ширина                                            | 180 mm            |
| USB Type-C ports quantity (receiver)               | 2                             | Глубина                                           | 95 mm             |
| Количество портов USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 4                             | Высота                                            | 23 mm             |
| Гнездо входа постоянного тока (DC)                 | ✓                             | Вес                                               | 1,58 kg           |
| Материал контакта                                  | Фосфористая бронза            | <b>Содержимое упаковки</b>                        |                   |
| Покрытие контактов разъема                         | Золото                        | Поставляемые кабели                               | Постоянный ток    |
| Материал разъема                                   | Золото                        | Инструкция                                        | ✓                 |
| Дизайн                                             |                               | <b>Данные об упаковке</b>                         |                   |
| Цвет товара *                                      | Черный                        | Тип упаковки                                      | Коробочная версия |
| Материал корпуса                                   | Металл                        | Ширина упаковки                                   | 260 mm            |
| Светодиодные индикаторы                            | ✓                             | Глубина упаковки                                  | 252 mm            |
|                                                    |                               | Высота упаковки                                   | 85 mm             |
|                                                    |                               | Объем упаковки                                    | 1890 cm³          |

| Дизайн                  |                                   | Сертификаты                                 |                                                            |
|-------------------------|-----------------------------------|---------------------------------------------|------------------------------------------------------------|
| Сертификация            | CE, UKCA, FCC, RoHS & REACH, CP65 | Compliance certificates                     | CE, Федеральная комиссия по связи (ФКС), REACH, RoHS, UKCA |
| Энергопитание           |                                   | Логистические данные                        |                                                            |
| Внешний адаптер питания | ✓                                 | Код гармонизированной системы описания (HS) | 85176990                                                   |
| Выходное напряжение     | 24 V                              |                                             |                                                            |



4002888393652

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.