

TP-Link InSight S345S Bullet IP security camera Outdoor 2688 x 1520 pixels Ceiling/Wall/Pole

Brand : TP-Link

Product code: INSIGHT S345S(4MM)

Product name : InSight S345S



- AI-ISP Powered Ultra Low-Light Color Night Vision
- 4MP Super-High Definition
- People & Vehicle Analytics
- Human & Vehicle Classification
- Smart Detection
- Two-Way Audio
- Smart Video Enhancement Technology
- Flexible Alarm In/Out Devices Integration
- IP67 Weatherproof
- H.265+ Compression Technology

VIGI 4MP Outdoor ColorPro 2.0 Bullet Network Camera

TP-Link InSight S345S. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Bullet. Minimum illumination: 0.0005 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 95°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.79 mm (1 / 1.79"). Detect distance: 76 m, Observe distance: 29 m, Recognize distance: 14 m

Performance		Video	
Type *	IP security camera	Highlight Compensation (HLC)	✓
Placement supported *	Outdoor	Region of Interest (ROI) encoding	✓
Connectivity technology *	Wired	Smart IR	✓
Wide Dynamic Range (WDR)	✓	Audio	
Infrared (IR) cut-off filter	✓	Built-in speaker(s)	✓
Alarm input/output	✓	Audio system	2-way
Dynamic range	120 dB	Signal-to-Noise Ratio (SNR)	52 dB
Design		Built-in microphone	✓
Form factor *	Bullet	Network	
Mounting type *	Ceiling/Wall/Pole	Ethernet LAN *	✓
Product colour *	White	Ethernet interface type	Fast Ethernet
Housing material	Metal	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP, SMTP, SNMP, RTMP
International Protection (IP) code	IP67	Wi-Fi *	✗
Camera		Bluetooth *	✗
Minimum illumination	0.0005 lx	Storage	
Angle of rotation	360°	Built-in HDD *	✗
Lens viewing angle, horizontal	95°	Card reader integrated	✓
Lens viewing angle, vertical	51°	Compatible memory cards	MicroSD (TransFlash)
Lens viewing angle, diagonal	115°	Maximum memory card size	512 GB
Tilt angle range	0 - 75°	Ports & interfaces	
Pan range	0 - 360°	Ethernet LAN (RJ-45) ports	1
Camera shutter speed	1/3 - 1/10000 s	Security	
Image sensor		Alarm input channels	1
Optical sensor size	25.4 / 1.79 mm (1 / 1.79")		
Progressive scan	✓		
Sensor type *	CMOS		

Lens system		Security	
Number of lenses *	1	Alarm output channels	1
Detect distance	76 m	Password protection	✓
Observe distance	29 m	Video motion detection	✓
Recognize distance	14 m	Active tampering alarm	✓
Maximum aperture number	1	IP address filtering	✓
Identify distance	7 m	HTTPS encryption	✓
Fixed focal length	4 mm		
Night vision			
Night vision *	✓	Intelligent Video Surveillance (IVS) system features	Abandoned object, Abnormal sound detection, Human detection, Intrusion, Line crossing detection, Region entrance detection, Region exiting detection, Scene change, Vehicle detection
Night vision distance	30 m		
LED type	IR/White	Digest authentication	✓
Number of illumination LEDs	2	Management features	
Infra-red wavelength	850 nm	Web browser	✓
Video		Cloud-managed *	✓
Maximum resolution *	2688 x 1520 pixels	Power	
Total megapixels *	4 MP	Power source type *	DC, PoE
Video compression formats	H.264, H.264+, H.265, H.265+	DC output voltage	12
	320 x 240, 352 x 288, 640 x 360, 640 x 480 (VGA), 704 x 576, 848 x 480, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520	Operational conditions	
Supported graphics resolutions		Operating temperature (T-T)	-30 - 60 °C
		Storage temperature (T-T)	-40 - 60 °C
Video streaming	✓	Operating relative humidity (H-H)	0 - 95%
Noise reduction	✓	Storage relative humidity (H-H)	0 - 95%
Noise reduction technology	3D noise reduction	Weight & dimensions	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Diameter	6.6 cm
		Length	191 mm
Bit rate	Main Stream: 256 Kbps - 6 Mbps; Sub-Stream: 64 Kbps - 1024 Kbps	Weight	600 g
Back Light Compensation (BLC)	✓	Sustainability	
		Compliance certificates	BSMI, CE, Federal Communications Commission (FCC), Industry Canada (IC), KC, VCCI
		Packaging content	
		Number of cameras *	1
		Mounting kit	✓
		Manual	✓



8885020625608



1210002608299



0810142822930



810142822930

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.