



Canon EOS R6 Mark III + RF 24-105mm F4 L IS USM MILC 32.5 MP CMOS 6960 x 4640 pixels Black

Brand : Canon

Product family: EOS

Product code: 7084C012

Product name : R6 Mark III + RF 24-105mm F4 L IS USM

- 32.5 megapixel resolution
- 8.5-stop IS
- Up to 7K RAW video
- 40 frames per second
- Wi-Fi** and Bluetooth
- Open Gate
- Dual Pixel CMOS AF II
- CFexpress and UHS-II SD card slots
- RF 24-105mm F4 L IS USM

EOS R6 Mark III + RF 24-105mm F4 L IS USM

Canon EOS R6 Mark III + RF 24-105mm F4 L IS USM. Camera type: MILC, Megapixel (approx.): 32.5 MP, Sensor type: CMOS, Maximum image resolution: 6960 x 4640 pixels. ISO sensitivity (max): 102400. Focal length range: 24 - 105 mm. Fastest camera shutter speed: 1/16000 s. Wi-Fi. Maximum video resolution: 6960 x 3672 pixels. Display diagonal: 7.62 cm (3"), Touchscreen. Viewfinder type: Electronic. Weight: 609 g. Product colour: Black



Picture quality		Viewfinder	
Image sensor aspect ratio	3:2	Viewfinder frame rate (smooth mode)	120 fps
Camera type *	MILC	Viewfinder information	AE lock, AEB, AF method, AF operation, AF point information, Anti-flicker shooting, Aperture, Auto Lighting Optimizer, Battery level, Bluetooth function, Digital Lens Optimizer, Drive mode, Electronic level, Exposure compensation, Exposure level indicator, Exposure simulation, FE lock, FEB, Flash-ready, Focus distance scale, HDR shooting, High-speed sync, Highlight tone priority, Histogram, ISO speed, Image Quality, Maximum burst, Metering mode, Multiple-function lock warning, Multiple-exposure shooting, Number of self-timer shooting, Shooting mode, Shutter speed, Still photo cropping, Vertical exposure scale, White balance, Wi-Fi function
Megapixel (approx.) *	32.5 MP		
Sensor type *	CMOS		
Sensor cleaning system	EOS integrated		
Maximum image resolution *	6960 x 4640 pixels		
Sensor cleaning system name	EOS Integrated Cleaning System		
Still image resolution(s) *	6960 x 4640, 4800 x 3200, 3472 x 2320, 2400 x 1600, 4320 x 2880, 6160 x 4640, 4256 x 3200, 3072 x 2320, 2112 x 1600, 6960 x 3904, 4800 x 2688, 3472 x 1952, 2400 x 1344, 3200 x 3200, 2320 x 2320, 1600 x 1600		
Supported aspect ratios	1:1, 2:3, 3:2, 3:4, 4:3, 16:9		
Total megapixels	34.2 MP		
Image sensor size (W x H)	35.9 x 23.9 mm		
Built-in low-pass filter	✓		
Colour filter type	Primary colour filter	Depth of field preview	✓
Sensor shift IS	✓	Viewfinder resolution (approx.)	3690000 pixels
Sensor shift IS number of stops (max)	8.5	Ports & interfaces	
Image formats supported *	HEIF, JPEG, Raw	PictBridge *	✗
Lens system		USB version *	3.2 Gen 2 (3.1 Gen 2)
Focal length range	24 - 105 mm	USB connector	USB Type-C
Minimum aperture number	22	HDMI *	✓
Maximum aperture number	4	HDMI connector type	Full-size
Lens structure (elements/groups)	18/14	Microphone in	✓
Number of diaphragm blades	9	Headphone outputs	1
Lens mount interface	Canon RF	Network	
Focusing		Bluetooth *	✓
Focus *	TTL	Bluetooth version	5.1
Focus adjustment *	Auto/Manual	Wi-Fi *	✓
Focusing system	Dual Pixel CMOS AF II	Wi-Fi standards	Wi-Fi 5 (802.11ac)

Focusing		Camera	
Auto focusing (AF) modes *	AI Focus, One Shot Focus, Servo Auto Focus	White balance *	Cloudy, Custom modes, Daylight, Shade, Tungsten
Auto Focus (AF) object detection	Bird, Body, CAT, Dog, Eye, Face, Head, Horse, People, Train, Vehicle	White balance compensation (Blue/Amber)	±9
Face tracking	✓	White balance compensation (Magenta/Green)	±9
Auto Focus (AF) points	4	Custom white balance	✓
Auto Focus (AF) points selection	Auto	Number of custom white balance settings	4
Auto Focus (AF) points manual selection	AF point expansion 4 points, AF point expansion surrounding, Flexible zone AF 1-3	Scene modes *	Children, Close-up (macro), Food, Group photo, HDR backlight control, Handheld night scene, Landscape, Night portrait, Panning, Panorama, Portrait, Silent shutter, Smooth skin, Sports
Auto Focus (AF) lock	✓		
Auto Focus (AF) assist beam	✓		
Auto Focus (AF) working range	EV -6.5 – 21		
Exposure		Shooting modes *	Intelligent auto, Manual, Scene
ISO sensitivity (min) *	100	Self-timer delay *	2,10 s
ISO sensitivity (max) *	102400	Playback zoom (max)	10x
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE	Histogram	✓
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)	Live view	✓
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot	High Dynamic Range (HDR) video processing	✓
Auto Exposure (AE) lock	✓	HEIF to JPEG conversion	✓
Number of measurement zones	384	Camera drive modes	Continuous high, Continuous high+, Continuous low, Self-timer
Exposure bracketing (AEB)	± 3EV (1/2EV; 1/3EV stop)	File numbering options	Auto-reset, Consecutive numbering, Manual reset
Anti-flicker shooting	✓	Number of file naming user presets	2
Shutter		Histogram options	Brightness, RGB
Fastest camera shutter speed *	1/16000 s	Highlight alert	✓
Slowest camera shutter speed *	30 s	Erase options	Select range
Camera shutter type	Electronic	Firmware upgradeable	✓
Shutter release type	Electromagnetic	Tripod mounting supported *	✓
Flash		Built-in processor	✓
Flash modes *	Auto, Manual	Image processor	DIGIC X
Flash exposure lock	✓	Windows operating systems supported	Windows 11
Flash exposure compensation	✓	Mac operating systems supported	Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Flash exposure correction	±3EV (1/3 EV step)	Design	
Shoe mounting point	✓	Market segment *	Professional
Shoe mounting point type	Hot shoe	Product colour *	Black
Flash exposure bracketing	✓	Dustproof	✓
Video		Waterproof	✓
Video recording *	✓	Material	Magnesium
Maximum video resolution *	6960 x 3672 pixels	Battery	
Video resolutions	1920 x 1080,2048 x 1080,3840 x 2160,4096 x 2160	Battery technology *	Lithium-Ion (Li-Ion)
Video formats supported	H.265, MP4	Battery life (display)	620 shots
Dual card video recording	✓	Battery life (viewfinder)	390 shots
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit	Battery type	LP-E6P
Audio		Battery level indicator	✓
Built-in microphone *	✓	Battery level indicator number of levels	6
Built-in speaker(s)	✓	Power	
Memory		USB Type-C charging port *	✓
Compatible memory cards *	CFexpress 2.0 Type B, SD, SDHC, SDXC	Operational conditions	
Memory slots	2	Operating temperature (T-T)	0 - 40 °C
Maximum memory card size	8 TB	Weight & dimensions	
Display		Width	138.4 mm
Display *	LCD		
Touchscreen *	✓		

Display		Weight & dimensions	
Display diagonal *	7.62 cm (3")	Depth	88.4 mm
Display resolution	160000 dot	Height	98.4 mm
Viewing angle, horizontal	170°	Weight	609 g
Viewing angle, vertical	170°	Packaging data	
Anti-smudge coating	✓	Quantity per pack	1 pc(s)
Display brightness adjustment	✓	Package width	225 mm
Number of manual brightness adjustment levels	4	Package depth	282 mm
Viewfinder		Package height	188 mm
Viewfinder type	Electronic	Package weight	2.42 kg
Magnification	0.76x	Packaging content	
Viewfinder screen size	0.5"	Hand strap	✓
Viewfinder eyepoint (approx.)	2.3 cm	Power cord included	✓
		AC adapter included *	✓
		Battery charger included	✓
		Batteries included	✓
		Logistics data	
		Pallet gross length	120 cm
		Pallet gross width	80 cm
		Pallet gross height	110.5 cm
		Products per pallet layer	18 pc(s)
		Pallet gross weight	163 kg
		Layers per pallet	3 pc(s)
		Products per pallet	54 pc(s)
		Master (outer) case width	246 mm
		Master (outer) case length	588 mm
		Master (outer) case height	325 mm
		Master (outer) case gross weight	8.22 kg
		Products per master (outer) case	3 pc(s)



4549292246346

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.