



Lindy 43421 tīkla pagarinātājs Tīkla raidītājs un uztvērējs Melns

Zīmols : Lindy

Preces kods: 43421

Modeļa nosaukums : 43421

Lindy 43421. Tips: Tīkla raidītājs un uztvērējs, Maksimālais pārskaitījums attālums: 100 m, Datu pārsūtīšanas ātrums: 480 Mbit/s. Kontakta materiāls: Fosfora bronza, Konektora kontaktu apvalks: Zelts, Savienotāja materiāls: Zelts. Produkta krāsa: Melns, Apvalka materiāls: Metāls, Sertifikācija: CE, UKCA, FCC, RoHS & REACH, CP65. Izejas spriegums: 24 V, Izejas strāva: 3,75 A, Barošanas norāde: 5.5/2.1mm DC. Platums: 140 mm, Dziļums: 75 mm, Augstums: 23 mm



Darbības rādītāji		Energijas pārvaldība	
Tips *	Tīkla raidītājs un uztvērējs	Izejas spriegums	24 V
Maksimālais pārskaitījums attālums *	100 m	Izejas strāva	3,75 A
Datu pārsūtīšanas ātrums	480 Mbit/s	Power over Ethernet (PoE)	✓
Kabeļu tipi, kas ir atbalstīti	Cat6a	Barošanas norāde	5.5/2.1mm DC
Chipset (mikroshēmojums) (raidītājs)	VS6320	Iekļauto strāvas kontaktdakšu veidi	AU, EU, UK, US
Plug and Play	✓	Ārējās vides apstākļi	
Savienojamība		Darbības temperatūras amplitūda (T-T)	0 - 40 °C
Ethernet LAN (RJ-45) pieslēgvietu skaits	2	Uzglabāšanas temperatūras amplitūda (T-T)	-20 - 60 °C
RJ-45 portu skaits (raidītājs)	1	Darbības relatīvā mitruma amplitūda	10 - 90%
RJ-45 portu skaits (uztvērējs)	1	Uzglabāšanas relatīvā mitruma amplitūda	10 - 90%
USB Type-C portu skaits (raidītājs)	3	Svars&dimensijas	
USB Type-C portu skaits (uztvērējs)	2	Platums	140 mm
USB 3.2 Gen 1 (3.1 Gen 1) A tipa pieslēgvietu skaits	5	Dziļums	75 mm
DC ieejas ligzda	✓	Augstums	23 mm
Kontakta materiāls	Fosfora bronza	Svars	1,72 kg
Konektora kontaktu apvalks	Zelts	Iepakojuma saturs	
Savienotāja materiāls	Zelts	Pievienoti kabeli	USB Type-A - USB Type-B adapters
Dizains		Manuāls	✓
Produkta krāsa *	Melns	Informācija par iepakojumu	
Apvalka materiāls	Metāls	Iepakojuma tips	Kaste
LED indikatori	✓	Iepakojuma platums	270 mm
Sertifikācija	CE, UKCA, FCC, RoHS & REACH, CP65	Iepakojuma dziļums	245 mm
		Iepakojuma augstums	75 mm
		Vienības apjoms	2020 cm³

Enerģijas pārvaldība		Sertifikāti	
Ārējais jaudas adapteris	✓	Atbilstības sertifikāti	CE, Federālā komunikāciju komisija, REACH, RoHS, UKCA
Loģistiskie dati			
Harmonizētās sistēmas (HS) kods		85176990	



4002888434218

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.