



APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

Brand : APC

Product code: SMT750IC

Product name : APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, USB cable

APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 4.6 min, Typical backup time at half load: 15.8 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH, PEP, EOL




Features		Battery	
UPS topology *	Line-Interactive	Replacement battery cartridge	rbc48
Output power capacity *	0.75 kVA	Design	
Output power *	500 W	Form factor *	Tower
Waveform *	Sine	Cable length	1.83 m
Input operation voltage (min) *	151 V	Product colour *	Black
Input operation voltage (max) *	302 V	Display type	LCD
Input frequency *	50/60 Hz	LED indicators	Status
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Automatic Voltage Regulation (AVR)	✓	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	540 J	Operating relative humidity (H-H)	5 - 95%
Efficiency	98%	Storage relative humidity (H-H)	0 - 95%
Noise level	40 dB	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Auto-restart	✓	Certificates	
Ports & interfaces		Compliance certificates	RoHS
AC outlet types	C13 coupler	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH, PEP, EOL
Power plug	C14 coupler	Packaging content	
AC outlets quantity	6 AC outlet(s)	Cables included	USB cable
Number of output IEC jumpers	2	Management card included	✗
USB port	✓	Manual	✓
Ethernet LAN (RJ-45) ports	1	Quick installation guide	✓
SmartSlot	✓	Weight & dimensions	
SmartConnect port	✓	Width	138 mm
Battery		Depth	358 mm
Battery technology	Sealed Lead Acid (VRLA)		
Typical backup time at full load	4.6 min		

Battery		Weight & dimensions	
Typical backup time at half load	15.8 min	Height	157 mm
Battery life (max)	5 year(s)	Weight	13.2 kg
Battery recharge time	3 h	Packaging data	
Hot-swap battery	✓	Bundled software	PowerChute Serial Edition
Automatic battery test	✓	Package width	278 mm
Cold start	✓	Package depth	499 mm
		Package height	301 mm
		Package weight	14.2 kg
		Logistics data	
		Products per pallet	24 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	639.93



0731304340317



731304340317

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.