

GIGABYTE GP-UD850GM PG5 power supply unit 850 W 20+4 pin ATX ATX Black


Brand : GIGABYTE

Product code: GP-UD850GM PG5

Product name : GP-UD850GM PG5

- Ultra Durable
- Main Japanese capacitors
- Enhanced thermal solution
- 120mm smart hydraulic bearing (HYB) fan
- OVP/OPP/SCP/UEP/OC/OTP protection
- Support PCIe Gen 5.0 graphics card
- High-quality native 16-pin cable supports 600W output
- 80 PLUS Gold certified
- Fully modular design
- Compact design

- 5 years warranty (Adjusted according to different regions)
ATX 12V, Active PFC, 100-240 Vac, 12-6A, 60-50 Hz, 850W, 150 x 140 x 86 mm, 120mm Hydraulic Bearing(HYB)fan, 100-150ms
GIGABYTE GP-UD850GM PG5. Total power: 850 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: CPU, PATA, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	850 W	PCI Express power connectors (16-pin)	1
AC input voltage *	100 - 240 V	PCI Express power cable length	70 cm
AC input frequency	50 - 60 Hz	CPU power connector (4+4 pin)	✓
Input current	12 - 6 A	ATX power connector (20+4 pin)	✓
Maximum input current (@110V)	6 A	PCI Express connector	✓
Maximum input current (@220V)	12 A	Cabling type	Fully-Modular
Power Factor Correction (PFC) type	Active	Performance	
Combined power (+3.3V)	105 W	80 PLUS certification *	80 PLUS Gold
Combined power (+12V)	850 W	Purpose *	PC
Combined power (+5V)	105 W	Power supply unit (PSU) form factor	ATX
Combined power (-12V)	3.6 W	*	
Combined power (+5Vsb)	15 W	Noise level	40 dB
Max output current (+3.3V)	20 A	Mean time between failures (MTBF)	100000 h
Max output current (+12V)	70.8 A	Design	
Max output current (+5V)	20 A	Product colour	Black
Max output current (-12V)	0.3 A	Cooling type	Active
Max output current (+5Vsb)	3 A	Fan diameter	12 cm
Hold time	16 ms	Number of fans	1 fan(s)
Efficiency	90%	Fan location	Top
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Illumination	✗
Ports & interfaces		Packaging content	
Motherboard power connector *	20+4 pin ATX	Cables included	CPU, PATA, Peripheral (Molex), SATA
Motherboard power cable length	61 cm	Cable tie(s) included	✓
Number of SATA power connectors	8	Certificates	
Number of PATA power connectors	3	Compliance certificates	CCC, CE, Federal Communications Commission (FCC), RoHS
SATA power cable length	150,600 mm		

Ports & interfaces		Weight & dimensions	
Peripheral (Molex) power connectors (4-pin) *	2	Width	150 mm
Peripheral (Molex) power cable length	200,600 mm	Depth	140 mm
PCI Express power connectors (6+2 pin)	4	Height	85 mm
		Packaging data	
		Package type	Box
		Logistics data	
		Warranty period	5 year(s)



4719331553104

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.