



Dahua Technology CS4228-24GT-240 tīkla pārslēgs Vadīts L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Melns

Zīmols : Dahua Technology

Preces kods: CS4228-24GT-240

Modeļa nosaukums : CS4228-24GT-240

Dahua Technology CS4228-24GT-240. Slēdža tips: Vadīts, Slēdža līmenis: L2. Basic switching RJ-45 Ethernet portu veids: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet portu daudzums: 26, Instalēto SFP moduļu skaits: 2. Adrešu tabulas izmērs: 8000 ieraksti, Komutācijas ietilpība: 56 Gbit/s. Tīkla standarts: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE.... Power over Ethernet (PoE). Statņa montāža

Vadības īpašības		Energijas pārvaldība	
Slēdža tips *	Vadīts	Jaudas avots *	AC/DC/PoE
Slēdža līmenis	L2	Mainstrāvas ievades spriegums	100 - 240 V
Tīkla bāzēts menedžments	✓	Mainstrāvas ievades frekvence	47/63 Hz
Pārvaldība no mākoņpakalpojuma	✓	Ieejas strāva	4 A
Savienojamība		Strāvas patēriņš (maks)	265 W
Basic switching RJ-45 Ethernet portu daudzums *	26	Power over Ethernet (PoE)	
Basic switching RJ-45 Ethernet portu veids *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) *	✓
Instalēto SFP moduļu skaits *	2	Power over Ethernet (PoE) pieslēgvietu skaits	24
Tīklošana		Kopējais Power over Ethernet (PoE) budžets	240 W
Tīkla standarts *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Ārējās vides apstākļi	
10G atbalsta *	✗	Darbības temperatūras amplitūda (T-T)	-10 - 55 °C
Plūsmas kontroles atbalsts	✓	Uzglabāšanas temperatūras amplitūda (T-T)	-40 - 70 °C
Atbalsta VLAN	✓	Darbības relatīvā mitruma amplitūda	5 - 95%
Virtuālā LAN īpašības	Port-based VLAN	Uzglabāšanas relatīvā mitruma amplitūda	5 - 95%
VLAN skaits	32	Svars & dimensijas	
Datu pārraide		Platums	440 mm
Komutācijas ietilpība *	56 Gbit/s	Dziļums	220 mm
Pakešu apstrādes jauda	41,66 miljons pakešu sekundē	Augstums	44 mm
Adrešu tabulas izmērs *	8000 ieraksti	Svars	2,5 kg
Jumbo Frames atbalsts	✓	Informācija par iepakojumu	
Jumbo rāmji	15360	Iepakojuma platums	540 mm
Drošība		Iepakojuma dziļums	342 mm
DHCP īpašības	DHCP client	Iepakojuma augstums	90 mm
Dizains		Iepakojuma svars	3,15 kg
Statņa montāža *	✓		
Produkta krāsa	Melns		
Apvalka materiāls	Tērauds		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.