

Epson EB-W55

Brand : Epson

Product code: V11HB58040

Product name : EB-W55

- High visibility large display: Enjoy an impressive display of up to 320 inches, perfect for immersive home entertainment or dynamic business presentations with split-screen functionality.
  - Brighter, vivid projection: Epson's 3LCD technology delivers an equally high white and Colour Light Output (CLO) of 4,000 lumens, so that you can experience vivid and lifelike images
  - Long-lasting solution: With this model's long-lasting lamp light source, you can enjoy a big screen experience for up to 18 years\*
  - Built-in speakers: The built-in 2W mono speaker delivers powerful sound, ensuring clear audio even in larger rooms, so you don't need to prepare additional speakers
  - Enhanced connectivity: Equipped with 2x HDMI ports and WiFi 6E to easily connect multiple devices and ensure faster communication speeds\*
  - Refreshingly easy setup: Enjoy effortless setup with the auto power-on function, which detects signals from connected devices and starts automatically, ensuring an easy to use experience
- EB-W55



| Projector                                    |                             | Multimedia                        |                  |
|----------------------------------------------|-----------------------------|-----------------------------------|------------------|
| Screen size compatibility *                  | 838.2 - 8128 mm (33 - 320") | Built-in speaker(s) *             | ✓                |
| Projection distance                          | 1.68 - 2.02 m               | RMS rated power                   | 2 W              |
| Contrast ratio (dynamic)                     | 16000:1                     | Number of built-in speakers       | 1                |
| Projector brightness *                       | 4000 ANSI lumens            | Design                            |                  |
| Projection technology *                      | 3LCD                        | Market positioning *              | Home cinema      |
| Projector native resolution *                | WXGA (1200x800)             | Product colour *                  | White            |
| Contrast ratio (typical) *                   | 16000:1                     | Placement                         | Ceiling, Desktop |
| Native aspect ratio *                        | 16:10                       | Cable lock slot                   | ✓                |
| Projector brightness (economic mode)         | 2600 ANSI lumens            | Cable lock slot type              | Kensington       |
| Vertical scan range                          | 100 - 120 Hz                | Display                           |                  |
| Keystone correction, horizontal              | ±30°                        | Built-in display *                | ✗                |
| Keystone correction, vertical                | ±30°                        | Power                             |                  |
| Matrix size                                  | 1.5 cm (0.59")              | Power source *                    | AC               |
| Light source                                 |                             | Power consumption (typical) *     | 284 W            |
| Light source type *                          | Lamp                        | Power consumption (PowerSave)     | 0.3 W            |
| Service life of light source *               | 6000 h                      | Power consumption (economy mode)  | 181 W            |
| Service life of light source (economic mode) | 12000 h                     | AC input voltage                  | 100 - 240 V      |
| Lamp type                                    | UHE                         | AC input frequency                | 50 - 60 Hz       |
| Lamp power                                   | 210 W                       | Operational conditions            |                  |
| Lens system                                  |                             | Operating temperature (T-T)       | 5 - 35 °C        |
| Focus *                                      | Manual                      | Storage temperature (T-T)         | -10 - 60 °C      |
| Focal length range                           | 16.9 - 20.28 mm             | Operating relative humidity (H-H) | 41 - 95%         |
| Aperture range (F-F)                         | 1.49 - 1.72                 | Storage relative humidity (H-H)   | 10 - 90%         |
| Zoom type                                    | Manual                      | Weight & dimensions               |                  |
| Zoom ratio                                   | 1.2:1                       | Width                             | 302 mm           |
| Throw ratio                                  | 1.30 - 1.56:1               | Depth                             | 237 mm           |
| Video                                        |                             | Height                            | 92 mm            |
| Analog signal format system *                | Not supported               | Weight *                          | 2.6 kg           |
| Full HD *                                    | ✗                           |                                   |                  |

| Video                         |                                              | Weight & dimensions         |                                                                                                                                                                                                              |
|-------------------------------|----------------------------------------------|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3D *                          | ✗                                            | Package width               | 330 mm                                                                                                                                                                                                       |
| Colour modes (2D)             | Cinema, Dynamic                              | Package depth               | 380 mm                                                                                                                                                                                                       |
| Video colour modes            | Blackboard, Cinema, Dynamic, Photo, sRGB     | Package height              | 150 mm                                                                                                                                                                                                       |
|                               |                                              | Package weight              | 3.5 kg                                                                                                                                                                                                       |
| Ports & interfaces            |                                              | Packaging content           |                                                                                                                                                                                                              |
| Service port type             | USB Type-B                                   | Remote control included *   | ✓                                                                                                                                                                                                            |
| USB 2.0 Type-A ports quantity | 1                                            | Batteries included          | ✓                                                                                                                                                                                                            |
| HDMI ports quantity *         | 2                                            | Cables included             | AC                                                                                                                                                                                                           |
| DVI port *                    | ✗                                            |                             |                                                                                                                                                                                                              |
| Network                       |                                              | Technical details           |                                                                                                                                                                                                              |
| Smart TV *                    | ✗                                            | Other features              | A/V mute, Auto source search, Built-in speaker, Horizontal and vertical keystone correction, Long lamp life, Quick Corner, Split-Screen-Function, Wireless LAN capable, iProjecton set-up by scanning a code |
| Ethernet LAN *                | ✗                                            |                             |                                                                                                                                                                                                              |
| Wi-Fi *                       | ✓                                            | Mobile app support          | ✓                                                                                                                                                                                                            |
| Wi-Fi standards               | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n) |                             |                                                                                                                                                                                                              |
| Storage                       |                                              | Power consumption           | 284 Watt (Normal On-Mode), 181 Watt (Eco On-Mode), 332 Watt (Normal Peak-mode), 231 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby)                                                                   |
| Card reader integrated *      | ✗                                            |                             |                                                                                                                                                                                                              |
| Features                      |                                              | Logistics data              |                                                                                                                                                                                                              |
| Interactive *                 | ✗                                            | Quantity per pack           | 1 pc(s)                                                                                                                                                                                                      |
| Noise level (economic mode)   | 28 dB                                        |                             |                                                                                                                                                                                                              |
| Noise level (standby)         | 28 dB                                        | Other features              |                                                                                                                                                                                                              |
| Preset modes                  | Blackboard, Cinema, Dynamic, sRGB            | Option type                 | Ceiling mount, Document camera, Safety wire set                                                                                                                                                              |
| Noise level *                 | 37 dB                                        | Interface                   | USB 2.0 Type B (Service Only), HDMI in (2x), USB 2.0-A, Wireless LAN IEEE 802.11a/b/g/n                                                                                                                      |
| Country of origin             | Philippines                                  | Control panel               | 0.59 inch with C2 Fine                                                                                                                                                                                       |
| Password protection           | ✓                                            | Audio system                | Standard                                                                                                                                                                                                     |
|                               |                                              | Supported network protocols | IPv6, SNMP                                                                                                                                                                                                   |
|                               |                                              | Box contents                | Main unit, Power cable, Quick Start Guide, Remote control incl. batteries, Warranty card                                                                                                                     |
|                               |                                              | Security features           | Kensington lock, Padlock, Security cable hole, Password protection                                                                                                                                           |



8715946738581

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.