



## HP USB-C 100W G6 Dock Wired USB 3.2 Gen 2 (3.1 Gen 2) Type-C Black

**Brand :** HP

**Product code:** 9X3V1UT#ABB

**Product name :** USB-C 100W G6 Dock

HP USB-C 100W G6 Dock. Connectivity technology: Wired, Host interface: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 25000 Mbit/s. Product colour: Black, Colour name: Jet black, HD type: 4K Ultra HD. Power supply: 120 W, USB cable length: 1 m. Windows operating systems supported: Windows 10, Windows 11, Mac operating systems supported: MacOS, Other operating systems supported: ChromeOS




| Ports & interfaces                                |                                  | Software                               |                                                                                                                            |
|---------------------------------------------------|----------------------------------|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Connectivity technology *                         | Wired                            | Mac operating systems supported        | MacOS                                                                                                                      |
| Host interface *                                  | USB 3.2 Gen 2 (3.1 Gen 2) Type-C | Linux operating systems supported      | ✓                                                                                                                          |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 2                                | Other operating systems supported      | ChromeOS                                                                                                                   |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity   | 1                                | Operational conditions                 |                                                                                                                            |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity   | 1                                | Operating temperature (T-T)            | 0 - 35 °C                                                                                                                  |
| USB Power Delivery (USB PD)                       | ✓                                | Storage temperature (T-T)              | -20 - 60 °C                                                                                                                |
| USB Power Delivery up to                          | 100 W                            | Operating relative humidity (H-H)      | 10 - 90%                                                                                                                   |
| HDMI ports quantity *                             | 1                                | Storage relative humidity (H-H)        | 5 - 95%                                                                                                                    |
| HDMI version                                      | 2.1                              | Operating altitude                     | -15 - 3048 m                                                                                                               |
| DisplayPorts quantity                             | 2                                | Non-operating altitude                 | -15 - 12192 m                                                                                                              |
| DisplayPort version                               | 1.4                              | Sustainability                         |                                                                                                                            |
| Microphone in *                                   | ✗                                | Sustainable technologies and materials | Plastic-free packaging; At least 35% post-consumer recycled plastic; Packaged in at least 35% recycled corrugated material |
| DC-in jack                                        | ✗                                | Weight & dimensions                    |                                                                                                                            |
| Network                                           |                                  | Width                                  | 121 mm                                                                                                                     |
| Ethernet LAN *                                    | ✓                                | Depth                                  | 121 mm                                                                                                                     |
| Ethernet LAN (RJ-45) ports                        | 1                                | Height                                 | 51 mm                                                                                                                      |
| Ethernet LAN data rates                           | 25000 Mbit/s                     | Weight                                 | 680 g                                                                                                                      |
| Performance                                       |                                  | Packaging data                         |                                                                                                                            |
| Colour name                                       | Jet black                        | Package width                          | 396 mm                                                                                                                     |
| Card reader integrated *                          | ✗                                | Package depth                          | 950 mm                                                                                                                     |
| HD type                                           | 4K Ultra HD                      | Package height                         | 1710 mm                                                                                                                    |
| Maximum digital resolution                        | 3840 x 2160 pixels               | Package weight                         | 1.09 kg                                                                                                                    |
| Maximum refresh rate                              | 120 Hz                           | Packaging content                      |                                                                                                                            |
| Cable lock slot                                   | ✓                                | Warranty card                          | ✓                                                                                                                          |
| Cable lock slot type                              | Nano                             |                                        |                                                                                                                            |
| Product colour *                                  | Black                            |                                        |                                                                                                                            |
| LED indicators                                    | Power                            |                                        |                                                                                                                            |
| Country of origin                                 | China, Thailand                  |                                        |                                                                                                                            |

| Performance                         |                        | Technical details                        |                                                                           |
|-------------------------------------|------------------------|------------------------------------------|---------------------------------------------------------------------------|
| HP segment                          | Business               | Box contents                             | HP USB-C 100W G6 Dock; 120 W power adapter; Product notice; Warranty card |
| Power                               |                        |                                          |                                                                           |
| Power supply                        | 120 W                  | Other features                           | Windows 11; Windows 10; macOS; Linux; ThinPro; ChromeOS                   |
| USB cable length                    | 1 m                    |                                          |                                                                           |
| Wireless charging                   | ✗                      |                                          |                                                                           |
| Software                            |                        |                                          |                                                                           |
| Windows operating systems supported | Windows 10, Windows 11 | Pallet dimensions (W x D x H) (imperial) | 1199.9 x 997.5 x 145 mm (47.2 x 39.3 x 5.71")                             |
|                                     |                        | Pallet dimensions (W x D x H)            | 1200 x 1000 x 145 mm                                                      |
|                                     |                        | UNSPSC-code                              | 43211602                                                                  |



0198415314048



198415314048



5715328201484

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.