



## TP-Link Omada SFP 1000BASE-SX LC MiniGBIC Mm

**Brand :** TP-Link

**Product family:** Omada

**Product code:** TL-SM311LM

**Product name :** SFP  
1000BASE-SX LC MiniGBIC Mm

- Multi-mode MiniGBIC module  
- Applied to T3700G-28TQ, TL-SG5412F/TL-SG5428, TL-SL5428E, TL-SG3210/TL-SG3216/TL-SG3424/TL-SG3424P, TL-SL3428/TL-SL3452, TL-SG2210P/TL-SG2216/TL-SG2424/TL-SG2424P/TL-SG2452, TL-SL2210/TL-SL2218/TL-SL2428/TL-SL2452 and MC220L  
SFP 1000BASE-SX LC MiniGBIC Mm

TP-Link Omada SFP 1000BASE-SX LC MiniGBIC Mm:

### What This Product Does

The TL-SM311 series Fiber Module Cards are introduced for extending transfer distance. Attached to our managed/smart switches, they can extend the distance to several kilometers even tens of kilometers which can basically satisfy the distance requirement of LAN. Users can choose whether and which items to use the fiber modules according to the demand in order to lower cost.

TP-Link Omada SFP 1000BASE-SX LC MiniGBIC Mm. SFP transceiver type: Fiber optic, Maximum data transfer rate: 1250 Mbit/s, Interface type: mini-GBIC/SFP. Product colour: Metallic. Input voltage: 3.3 V. Compliance certificates: RoHS, Certification: FCC, CE. Width: 55.4 mm, Depth: 13.7 mm, Height: 12.9 mm



| Performance                                     |                    | Operational conditions            |             |
|-------------------------------------------------|--------------------|-----------------------------------|-------------|
| SFP transceiver type *                          | Fiber optic        | Minimum operating temperature     | 0 °C        |
| Maximum data transfer rate *                    | 1250 Mbit/s        | Maximum operating temperature     | 70 °C       |
| Interface type *                                | mini-GBIC/SFP      | Operating temperature (T-T)       | 0 - 70 °C   |
| Single-mode fiber (SMF) supported               | ✗                  | Storage temperature (T-T)         | -40 - 80 °C |
| Multi-mode fiber (MMF) supported                | ✓                  | Operating relative humidity (H-H) | 10 - 90%    |
| Fiber optic connector                           | LC (UPC)           | Storage relative humidity (H-H)   | 5 - 90%     |
| Fiber cable diameters supported (core/cladding) | 50/125,62.5/125 µm | Weight & dimensions               |             |
| Maximum transfer distance                       | 550 m              | Width                             | 55.4 mm     |
| Wavelength                                      | 850 nm             | Depth                             | 13.7 mm     |
| Networking standards                            | IEEE 802.3z        | Height                            | 12.9 mm     |
| Features                                        |                    | Packaging content                 |             |
| Product colour                                  | Metallic           | Quantity per pack                 | 1 pc(s)     |
| Power                                           |                    | Packaging data                    |             |
| Input voltage                                   | 3.3 V              | User guide                        | ✓           |
| Certificates                                    |                    | Package width                     | 38 mm       |
| Compliance certificates                         | RoHS               | Package depth                     | 207 mm      |
| Certification                                   | FCC, CE            | Package height                    | 38 mm       |
|                                                 |                    | Package weight                    | 110 g       |
|                                                 |                    | Logistics data                    |             |
|                                                 |                    | Harmonized System (HS) code       | 85369010    |



0845973030209



845973030209



5053959235295



0873395090099



873395090099



8459730302090



0115971107426



115971107426



0168141555190



168141555190



0172304261453



172304261453



6935364030209



0731215283192



731215283192




0898029711225



898029711225



4054318718771



6213759771990




0717559350462



717559350462




1210002619295



0840460605151



840460605151



1210002612036

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.