



## TP-Link VIGI C230 Dome IP security camera Indoor & outdoor 2304 x 1296 pixels Ceiling

**Brand :** TP-Link

**Product code:** VIGI C230(4MM)

**Product name :** VIGI C230

VIGI 3MP Full-Color Dome Network Camera

TP-Link VIGI C230. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Dome. Minimum illumination: 0.005 lx, Lens viewing angle, horizontal: 89.1°, Lens viewing angle, vertical: 45.1°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.8 mm (1 / 2.8"). Lens diameter: 4 mm



| Performance                        |                          | Night vision                  |                                                                          |
|------------------------------------|--------------------------|-------------------------------|--------------------------------------------------------------------------|
| Type *                             | IP security camera       | Infra-red wavelength          | 850 nm                                                                   |
| Placement supported *              | Indoor & outdoor         | <b>Video</b>                  |                                                                          |
| Connectivity technology *          | Wired                    | Maximum resolution *          | 2304 x 1296 pixels                                                       |
| Wide Dynamic Range (WDR)           | ✓                        | Total megapixels *            | 3 MP                                                                     |
| Day/night mode                     | ✓                        | Video compression formats     | H.264, H.264+, H.265, H.265+                                             |
| Certification                      | CE/BSMI/VCCI/ONVIF       | Video streaming               | ✓                                                                        |
| Design                             |                          | Noise reduction               | ✓                                                                        |
| Form factor *                      | Dome                     | Noise reduction technology    | 3D noise reduction                                                       |
| Mounting type *                    | Ceiling                  | Image quality adjustment      | Brightness, Contrast, Mirror, Saturation                                 |
| Product colour *                   | White                    | Privacy masking               | ✓                                                                        |
| Housing material                   | Plastic                  | Bit rate                      | 64 Kbps to 4 Mbps                                                        |
| Protection features                | Waterproof               | Back Light Compensation (BLC) | ✓                                                                        |
| International Protection (IP) code | IP67                     | Highlight Compensation (HLC)  | ✓                                                                        |
| IK code                            | IK10                     | Smart IR                      | ✓                                                                        |
| Camera                             |                          | Network                       |                                                                          |
| Camera pan control                 | ✓                        | Ethernet LAN *                | ✓                                                                        |
| Minimum illumination               | 0.005 lx                 | Ethernet interface type       | Fast Ethernet                                                            |
| Lens viewing angle, horizontal     | 89.1°                    | Networking standards          | IEEE 802.3af, IEEE 802.3at                                               |
| Lens viewing angle, vertical       | 45.1°                    | Supported network protocols   | TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS |
| Lens viewing angle, diagonal       | 106.9°                   | <b>Storage</b>                |                                                                          |
| Pan range                          | 0 - 360°                 | Built-in HDD *                | ✗                                                                        |
| Image sensor                       |                          | Security                      |                                                                          |
| Number of sensors                  | 1                        | Password protection           | ✓                                                                        |
| Optical sensor size                | 25.4 / 2.8 mm (1 / 2.8") |                               |                                                                          |
| Progressive scan                   | ✓                        |                               |                                                                          |
| Sensor type *                      | CMOS                     |                               |                                                                          |

| Panoramic camera                                     |      | Security                    |                                                                         |
|------------------------------------------------------|------|-----------------------------|-------------------------------------------------------------------------|
| Digital Wide Dynamic Range (DWDR) (panoramic camera) | ✓    | Mirror                      | ✓                                                                       |
| Lens system                                          |      | Password reset via email    | ✓                                                                       |
| Number of lenses *                                   | 1    | Digest authentication       | ✓                                                                       |
| Lens diameter                                        | 4 mm | Power                       |                                                                         |
| Maximum aperture number                              | 1.6  | Power source type *         | DC, PoE                                                                 |
| Night vision                                         |      | DC output voltage           | 12                                                                      |
| Night vision *                                       | ✓    | Operational conditions      |                                                                         |
| Night vision distance                                | 30 m | Operating temperature (T-T) | -30 - 60 °C                                                             |
| B/W night vision distance                            | 30 m | Weight & dimensions         |                                                                         |
| LED type                                             | IR   | Width                       | 115 mm                                                                  |
|                                                      |      | Depth                       | 86 mm                                                                   |
|                                                      |      | Height                      | 115 mm                                                                  |
|                                                      |      | Features                    |                                                                         |
|                                                      |      | Basic event                 | Motion Detection, Camera Tampering Detection, Exception (Illegal Login) |
|                                                      |      | Packaging content           |                                                                         |
|                                                      |      | Number of cameras *         | 1                                                                       |



4895252501926

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.