

D-Link DMS-106XT tīkla pārslēgs Nepārvaldīts 2.5G Ethernet (100/1000/2500) Pelēks

Zīmols : D-Link

Preces kods: DMS-106XT

Modeļa nosaukums : DMS-106XT

D-Link DMS-106XT. Slēdža tips: Nepārvaldīts. Basic switching RJ-45 Ethernet portu veids: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet portu daudzums: 6. Adrešu tabulas izmērs: 4000 ieraksti, Komutācijas ietilpība: 45 Gbit/s. Tīkla standarts: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE.... DC ievades spriegums: 12 V



Vadības īpašības		Darbības rādītāji	
Slēdža tips *	Nepārvaldīts	Vidējais laiks starp kļūmēm (MTBF)	489941 h
Quality of Service (QoS) atbalsts	✓	Energijas pārvaldība	
Savienojamība		Maiņstrāvas ievades spriegums	100 - 240 V
Basic switching RJ-45 Ethernet portu daudzums *	6	DC ievades spriegums	12 V
Basic switching RJ-45 Ethernet portu veids *	2.5G Ethernet (100/1000/2500)	Ieejas strāva	1.5 A
2.5G Ethernet (vara) portu skaits	5	Strāvas patēriņš (maks)	10,6 W
10G Ethernet (vara) portu skaits	1	Power over Ethernet (PoE)	
Tīklošana		Power over Ethernet (PoE) *	✗
Tīkla standarts *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x	Ārējās vides apstākļi	
10G atbalsta *	✓	Darbības temperatūras amplitūda (T-T)	0 - 40 °C
Vara Ethernet kabeļu tehnoloģija	10BASE-T, 10GBASE-T, 100BASE-TX, 1000BASE-T	Uzglabāšanas temperatūras amplitūda (T-T)	-10 - 70 °C
Plūsmas kontroles atbalsts	✓	Darbības relatīvā mitruma amplitūda	10 - 95%
Auto MDI/MDI-X	✓	Uzglabāšanas relatīvā mitruma amplitūda	5 - 95%
Datu pārraide		Karstuma izkļiedēšana	36,17 BTU/h
Komutācijas ietilpība *	45 Gbit/s	Svars&dimensijas	
Adrešu tabulas izmērs *	4000 ieraksti	Platums	217 mm
Uzglabāt un pārsūtīt	✓	Dzīlums	163 mm
Dizains		Augstums	33 mm
Statņa montāža *	✗	Svars	680 g
Sakraujams *	✗	Ilgtspēja	
Produkta krāsa	Pelēks	Ilgtspējas atbilstība	✓
Apvalka materiāls	Alumīnijs	Sertifikāti	
LED indikatori	Aktivitāte, Link, Jauda	Atbilstības sertifikāti	CE, RoHS
Darbības rādītāji		Sertifikācija	FCC, RCM, BSMI, VCCI
Bez ventilatora	✓	Logistiskie dati	
		Harmonizētās sistēmas (HS) kods	85176990



0790069459818



790069459818

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.