

CyberPower PR2200ELCDSL nepārtrauktas barošanas avots (UPS) Line-Interactive 2,2 kilovoltampērs 1980 W 9 Maiņstrāvas izvade (-s)

Zīmols : CyberPower

Preces kods: PR2200ELCDSL

Modeļa nosaukums : PR2200ELCDSL

CyberPower PR2200ELCDSL. UPS topoloģija: Line-Interactive, Izejas jaudas kapacitāte (VA): 2,2 kilovoltampērs, Izejas jauda: 1980 W. Maiņstrāvas izeju tipi: C13 uzmava, C19 uzmava, Jaudas spraudnis: C20 uzmava, Izeju skaits: 9 Maiņstrāvas izvade (-s). Baterijas tehnoloģija: Noslēgts svina skābju (VRLA), Akumulatora ietilpība: 9 ampērstunda, Baterijas spriegums: 12 V. Formas faktors: Tower, Produkta krāsa: Melns, Ekrāna veids: LCD. Platums: 170 mm, Dziļums: 432 mm, Augstums: 221 mm



Īpašības		Savienojamība	
UPS topoloģija *	Line-Interactive	Emergency Power Off (EPO) konektors	✓
Izejas jaudas kapacitāte (VA) *	2,2 kilovoltampērs	Baterija	
Izejas jauda *	1980 W	Baterijas tehnoloģija	Noslēgts svina skābju (VRLA)
Viļņa forma *	Sinuss	Akumulatora ietilpība	9 ampērstunda
Ievades darbības spriegums (min) *	160 V	Baterijas spriegums	12 V
Ievades darbības spriegums (maks) *	283 V	Atbalstāmo bateriju skaits	4
Izejas frekvence *	50/60 Hz	Tipiskais dublējuma laiks pilnā ielādē	3 min
Automātiskā sprieguma regulēšana (AVR)	✓	Tipiskais dublējuma laiks pusielādē	12 min
Atbildes laiks	4 ms	Baterijas uzlādes laiks	8 h
Izvedes fāžu skaits	1	Automātiska akumulatora pārbaude	✓
Izvedes fāžu skaits	1	Dizains	
Emergency Power Off (EPO)	✓	Formas faktors *	Tower
EMI/RFI trokšņu filtrācija	✓	Produkta krāsa *	Melns
Aizsardzība pret pārspriegumu	✓	Ekrāna veids	LCD
Jaudas aizsardzības apraksts	Pārslodze	LED indikatori	✓
Skaņas signalizācija	✓	Svars&dimensijas	
Tīkla bāzēts menedžments	✓	Platums	170 mm
Vadības protokoli	SNMP, HTTP	Dziļums	432 mm
Auto-restartēšana	✓	Augstums	221 mm
Savienojamība		Svars	23,3 kg
Maiņstrāvas izeju tipi	C13 uzmava, C19 uzmava	Informācija par iepakojumu	
Jaudas spraudnis	C20 uzmava	Iekļautā programmatūra	PowerPanel Business Edition
Izeju skaits	9 Maiņstrāvas izvade (-s)	Papildus informācija	
USB 2.0 pieslēgvietu skaits	1	Izejas savienotāji	8 x IEC 320 C13, 1 x IEC 320 C19
Seriālo pieslēgvietu skaits	1	Nominālais izejas spriegums	230 V

Papildus informācija

Nominālais ieejas spriegums	230 V
Piemērots izmantošanai valstī/vietā	Eiropa



4712364146350

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.