



# Lindy 43159 хаб-разветвитель USB 3.2 Gen 1 (3.1 Gen 1) Type-A 5000 Мбит/с Черный

Производитель : Lindy

Код товара: 43159

Модель : 43159

Lindy 43159. Основной интерфейс: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, типы подключения хаба: USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Скорость передачи данных: 5000 Мбит/с, Цвет товара: Черный, Материал корпуса: Пластик. Power note: 3.5/1.35mm DC. Ширина: 80 mm, Глубина: 38 mm, Высота: 15 mm. Количество в упаковке: 1 шт, Ширина упаковки: 240 mm, Глубина упаковки: 200 mm



| Порты и интерфейсы                                 |                                  | Свойства                             |                                                       |
|----------------------------------------------------|----------------------------------|--------------------------------------|-------------------------------------------------------|
| Основной интерфейс *                               | USB 3.2 Gen 1 (3.1 Gen 1) Type-A | Сертификация                         | CE, UKCA, FCC, RoHS, REACH, California Proposition 65 |
| типы подключения хаба *                            | USB 3.2 Gen 1 (3.1 Gen 1) Type-A | <b>Энергопитание</b>                 |                                                       |
| Количество портов USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 4                                | Power note                           | 3.5/1.35mm DC                                         |
| Количество портов *                                | 4                                | <b>Вес и размеры</b>                 |                                                       |
| Гнездо входа постоянного тока (DC)                 | ✓                                | Ширина                               | 80 mm                                                 |
| <b>Свойства</b>                                    |                                  | Глубина                              | 38 mm                                                 |
| Скорость передачи данных *                         | 5000 Мбит/с                      | Высота                               | 15 mm                                                 |
| Цвет товара                                        | Черный                           | Вес                                  | 790 g                                                 |
| Материал корпуса                                   | Пластик                          | Connector 1 dimensions (WxDxH)       | 15 x 42 x 8 mm                                        |
| Светодиодные индикаторы                            | ✓                                | <b>Данные об упаковке</b>            |                                                       |
| Тип кабеля                                         | Round cable                      | Количество в упаковке                | 1 шт                                                  |
| Материал покрытия                                  | Никелевый                        | Ширина упаковки                      | 240 mm                                                |
| Размер провода по АКП                              | 24/24/20                         | Глубина упаковки                     | 200 mm                                                |
| Материал защитной оболочки кабеля                  | Поливинилхлорид                  | Высота упаковки                      | 70 mm                                                 |
| Длина кабеля                                       | 10 m                             | Масса брутто                         | 900 g                                                 |
| Диаметр кабеля                                     | 7 mm                             | Тип упаковки                         | Коробочная версия                                     |
| Материал проводника                                | Луженая медь                     | <b>Содержимое упаковки</b>           |                                                       |
| Материал контакта                                  | Латунь                           | Инструкция                           | ✓                                                     |
| Покрытие контактов разъема                         | Золото                           | <b>Условия эксплуатации</b>          |                                                       |
| Plug & Play                                        | ✓                                | Диапазон температур при эксплуатации | 0 - 50 °C                                             |
| Bend radius (min)                                  | 3,6 cm                           | Диапазон рабочих температур          | -20 - 60 °F                                           |
| Transmission medium                                | Витая пара                       | <b>Дизайн</b>                        |                                                       |
|                                                    |                                  | Экранирование кабеля                 | Майлар-алюминиевая фольга                             |

| Свойства            |                   | Логистические данные                           |          |
|---------------------|-------------------|------------------------------------------------|----------|
| Nominal attenuation | 0.064MHz - 0.08dB | Код гармонизированной системы<br>описания (HS) | 84719000 |
|                     | 0.256MHz - 0.11dB |                                                |          |
|                     | 0.512MHz - 0.13dB |                                                |          |
|                     | 0.772MHz - 0.15dB |                                                |          |
|                     | 1.0MHz - 0.20dB   |                                                |          |
|                     | 4MHz - 0.39dB     |                                                |          |
|                     | 8MHz - 0.57dB     |                                                |          |
|                     | 12MHz - 0.67dB    |                                                |          |
|                     | 24MHz - 0.95dB    |                                                |          |
|                     | 48MHz - 1.35dB    |                                                |          |
|                     | 96MHz - 1.90dB    |                                                |          |
|                     | 200MHz - 3.20dB   |                                                |          |
|                     | 400MHz - 5.80dB   |                                                |          |



4002888431590



5053866596458

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.