



APC Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Brand : APC

Product code: SRT1000XLI

Product name : Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

[APC Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit:](#)

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1000VA on-line tower UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with 1x IEC 320 C14 input and 6x IEC 320 C13 outlets. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. The UPS is compatible with SRTRK4 (4-post) and SRTRK3 (2-post) rail kits sold separately.




Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	1 kVA	Battery weight	29.6 kg
Output power *	1000 W	Design	
Waveform *	Sine	Form factor *	Rackmount/Tower
Input operation voltage (min) *	220 V	Rack capacity	2U
Input operation voltage (max) *	240 V	Cable length	1.8 m
Input frequency *	40/70 Hz	Cooling type	Active
Output operation voltage (min)	50 V	Built-in fan	✓
Output operation voltage (max)	240 V	Product colour *	Black
Output frequency	50/60 Hz	Display type	LCD
Surge energy rating	432 J	LED indicators	✓
Crest factor	3:1	International Protection (IP) code	IP20
ECO mode	✓	Operational conditions	
Emergency Power Off (EPO)	✓	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	2%	Storage temperature (T-T)	-20 - 50 °C
Noise level	50 dB	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3048 m
Audible alarm modes	Alarm when on battery, Battery replacement	Non-operating altitude	0 - 15240 m
Auto-restart	✓	Certificates	
Ports & interfaces		Compliance certificates	CE
AC outlet types	C13 coupler	Certification	CE, EAC

Ports & interfaces		Packaging content	
Power plug	C14 coupler	Cables included	USB cable
AC outlets quantity	12 AC outlet(s)	Management card included	✗
USB port	✓	Quick installation guide	✓
Serial interface	✓	Sustainability	
Serial interface type	RJ-45	Sustainability compliance	✓
Serial ports quantity	1	Sustainability certificates	Green Premium
SmartSlot	✓	Weight & dimensions	
SmartConnect port	✗	Width	85 mm
Battery		Depth	505 mm
Battery technology	Sealed Lead Acid (VRLA)	Height	432 mm
Battery voltage	48 V	Weight	20.5 kg
Typical backup time at full load	8 min	Battery width	59.4 cm
Typical backup time at half load	21 min	Battery depth	74.9 cm
Battery life (max)	5 year(s)	Battery height	24.6 cm
Battery recharge time	3 h	Logistics data	
Hot-swap battery	✓	Harmonized System (HS) code	85078000
Automatic battery test	✓	Total carbon footprint (kg of CO2e)	1839.69
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304340270



731304340270

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.