



D-Link DEM-410T tīkla raiduztvērēja modulis Varš 10000 Mbit/s SFP+



Zīmols : D-Link

Preces kods: DEM-410T

Modeļa nosaukums : DEM-410T

D-Link DEM-410T. SFP veids raiduztvērēja veids: Varš, Maksimālais datu pārraides ātrums: 10000 Mbit/s, Interfeisa tips: SFP+. Produkta krāsa: Zelts, Sudrabs, Vidējais laiks starp kļūmēm (MTBF): 217186 h. Ieejas spriegums: 3.3 V. Atbilstības sertifikāti: RoHS, Drošība: LVD, Sertifikācija: CE, FCC, VCCI. Platums: 13,7 mm, Dziļums: 68 mm, Augstums: 8,5 mm

Darbības rādītāji		Svars&dimensijas	
SFP veids raiduztvērēja veids *	Varš	Svars	20 g
Maksimālais datu pārraides ātrums *	10000 Mbit/s	Informācija par iepakojumu	
Interfeisa tips *	SFP+	Iepakojuma platums	74 mm
SFP raiduztvērēja standarts	T	Iepakojuma dziļums	131 mm
Maksimālais pārskaitījums attālumam	30 m	Iepakojuma augstums	49 mm
Ethernet/LAN savienojums	✓	Iepakojuma svars	64 g
Ethernet interfeisa tips	10 Gigabit Ethernet	Logistiskie dati	
Tīkla standarts	IEEE 802.3ab, IEEE 802.3an	Transportējamās kastes garums	36 cm
Ethernet LAN (RJ-45) pieslēgvietu skaits	1	Transportējamās kastes platums	26 cm
Šķiedras ethernet kabeļu tehnoloģija	10GBASE, 1000BASE	Transportējamās kastes augstums	31 cm
Īpašības		Transportēšanas kārbas neto svars	3,2 kg
Produkta krāsa	Zelts, Sudrabs	Daudzums transportējamā kastē	50 pcs
Vidējais laiks starp kļūmēm (MTBF)	217186 h	Paletes neto svars (aviotransportam)	272 kg
Enerģijas pārvaldība		Kastu skaits paletē (aviotransportam)	60 pcs
Ieejas spriegums	3.3 V	Skaits vienā paletē (aviotransportam)	3000 pcs
Sertifikāti		Paletes garums	102 cm
Atbilstības sertifikāti	RoHS	Paletes platums	122 cm
Drošība	LVD	Paletes svars (aviotransportam)	199 cm
Sertifikācija	CE, FCC, VCCI	Paletes bruto svars (jūras transportam)	272 kg
Ārējās vides apstākļi		Kastu skaits paletē (jūras transportam)	60 pcs
Darbības temperatūras amplitūda (T-T)	0 - 60 °C	Skaits vienā paletē (jūras transportam)	3000 pcs
Uzglabāšanas temperatūras amplitūda (T-T)	-40 - 85 °C	Paletes augstums (jūras transportam)	199 cm
Darbības relatīvā mitruma amplitūda	5 - 95%	Transportējamās kastes svars	4,2 kg
Uzglabāšanas relatīvā mitruma amplitūda	5 - 95%	Harmonizētās sistēmas (HS) kods	85369010
Svars&dimensijas			
Platums	13,7 mm		
Dziļums	68 mm		
Augstums	8,5 mm		



0790069442353



790069442353

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.