

TP-Link TL-MR3420 bezvadu rūteris Ātrais Ethernet Viena frekvenču josla (2.4 GHz) Melns, Balts

Zīmols : TP-Link

Preces kods: TL-MR3420

Modeļa nosaukums : TL-MR3420

TP-Link TL-MR3420. WAN savienojuma veids: RJ-45. Wi-Fi josla: Viena frekvenču josla (2.4 GHz), Wi-Fi standarts: Wi-Fi 4 (802.11n), WLAN datu pārraides ātrums (maks.): 300 Mbit/s. Ethernet LAN saskarnes tips: Ātrais Ethernet, Ethernet LAN datu pārsūtīšanas ātrums: 10,100 Mbit/s, Tīkla standarts: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3u. Ugusmūra drošība: NAT, SPI. Produkta veids: Galda rūteris, Produkta krāsa: Melns, Balts



WAN savienojums		Iepakojuma saturs	
Ethernet WAN *	✓	AC adapteris komplektā	✓
DSL WAN *	✗	Antena iekļauta	✓
SIM kartes slots *	✗	Ātrās instalācijas gids	✓
3G/4G USB modema saderība *	✓	Ilgspēja	
WAN savienojuma veids	RJ-45	Ilgspējas atbilstība	✓
Bezvadu LAN īpašības		Antena	
Wi-Fi josla *	Viena frekvenču josla (2.4 GHz)	Antenas forma *	Ārējs
Wi-Fi standarts *	Wi-Fi 4 (802.11n)	Antenas savienotāja tips	RP-SMA
WLAN datu pārraides ātrums (maks.) *	300 Mbit/s	Antenas sasniedzības līmenis (max)	5 dBi
Wi-Fi standartu	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Antenu daudzums	2
Modulācija	16-QAM, 64-QAM, CCK, DBPSK, DQPSK, OFDM	Antenas virziena veids	Omni-directional
Pārraides jauda		20 decibeli uz milivatu	
Tīklošana		Īpašības	
Ethernet/LAN savienojums *	✓	Programmaparatūra atjauninājama	✓
Ethernet LAN saskarnes tips *	Ātrais Ethernet	Energijas pārvaldība	
Ethernet LAN datu pārsūtīšanas ātrums	10,100 Mbit/s	Barošanas avota veids *	AC
Tīkla standarts	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3u	Izejas spriegums	12 V
Auto MDI/MDI-X	✓	Izejas strāva	1 A
Uztvērēja jutīgums		Ārējās vides apstākļi	
270M: -68dBm@10% PER, 130M: -68dBm@10% PER, 108M: -68dBm@10% PER, 54M: -68dBm@10% PER, 11M: -85dBm@8% PER, 6M: -88dBm@10% PER, 1M: -90dBm@8% PER		Darbības temperatūras amplitūda (T-T)	0 - 40 °C
		Uzglabāšanas temperatūras amplitūda (T-T)	-40 - 70 °C
		Darbības relatīvā mitruma amplitūda	10 - 90%

Savienojamība		Ārējās vides apstākļi	
Ethernet LAN (RJ-45) pieslēgvietu skaits *	4	Uzglabāšanas relatīvā mitruma amplitūda	5 - 95%
USB pieslēgvietā *	✓	Sistēmas prasības Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 98SE, Windows NT, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64 Linux operētājsistēma atbalstīta Mac operētājsistēmas atbalstītas	
USB 2.0 pieslēgvietu skaits	1		
DC ieejas ligzda	✓		
Vadības īpašības			
Tīkla bāzēts menedžments	✓		
WPS poga	✓		
Drošība			
Firewall	✓		
Ugusmūra drošība	NAT, SPI		
DDoS aizsardzība	✓		
Filtrēšana	✓		
MAC adreses filtrēšana	✓		
IP adreses filtrēšana	✓		
URL filtrēšana	✓		
Dizains			
Produkta krāsa	Melns, Balts		
Integrēts on/off slēdzis	✓		
Produkta veids *	Galda rūteris		
Sertifikāti			
Atbilstības sertifikāti	RoHS, Federālā komunikāciju komisija, CE		
Iepakojuma saturs			
Pievienoti kabeli	LAN (RJ-45)		
Svars&dimensijas			
Platums		204 mm	
Dziļums		138 mm	
Augstums		44 mm	
Informācija par iepakojumu			
Iepakojuma platums		315 mm	
Iepakojuma dziļums		240 mm	
Iepakojuma augstums		70 mm	
Iepakojuma svars		620 g	
Loģistiskie dati			
Harmonizētās sistēmas (HS) kods		85176990	



6935364051495



0854587033407



854587033407



0845973051495



845973051495

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.