



FSP VITA GM 750W barošanas avotu vienība 20+4 pin ATX ATX Meln

Zīmols : FSP

Preces kods: PPA7507902

Modeļa nosaukums : VITA GM 750W

FSP VITA GM 750W. Kopējā jauda: 750 W, Maiņstrāvas ievades spriegums: 100 - 240 V, Maiņstrāvas ievades frekvence: 50/60 Hz. Mātesplates strāvas konektors: 20+4 pin ATX, Mātesplates barošanas vada garums: 60 cm, SATA strāvas kabeļa garums: 500 mm. Mērķis, rezultāts: PC (dators), Strāvas padeves bloka (PSU) formas faktors: ATX, 80 PLUS sertifikācija: 80 PLUS Gold. Produkta krāsa: Melns, Dzesēšanas tips: Aktīvs, Ventilatora diametrs: 12 cm. Pievienoti kabeli: Centrālais procesors, Peripheral (Molex), SATA



Enerģijas pārvaldība

Kopējā jauda *	750 W
Maiņstrāvas ievades spriegums *	100 - 240 V
Maiņstrāvas ievades frekvence	50/60 Hz
Ieejas strāva	10-5 A
Strāvas faktora korekcija (PFC) veids	Aktīvs
Kopējā strāva (+3,3V)	100 W
Kopējā strāva (+12V)	750 W
Kopējā strāva (+5V)	100 W
Kopējā strāva (-12V)	3,6 W
Kopējā strāva (+5Vsb)	15 W
Maksimālā izvades strāva (+3.3V)	20 A
Maksimālā izvades strāva (+12V)	62,5 A
Maksimālā izvades strāva (+5V)	20 A
Maksimālā izvades strāva (-12V)	0,3 A
Maksimālā izvades strāva (+5Vsb)	3 A
Efektivitāte	90%
Jaudas aizsardzības apraksts	Pārstrāva, Pārslodze, Pārspriegums, Pārkaršana, Īssavienojums, Zem sprieguma

Savienojamība

Mātesplates strāvas konektors *	20+4 pin ATX
Mātesplates barošanas vada garums	60 cm

Savienojamība

SATA strāvas savienotāju skaits	8
SATA strāvas kabeļa garums	500 mm
Perifērās (Molex) strāvas savienotāji (4-pin) *	4
PCI Express strāvas konektors (6+2 tapu)	4
CPU barošanas savienotājs (4 + 4 pin)	✓
CPU strāvas kabeļa garums	70 cm
Kabeļu tips	Pilnībā modulāra uzbūve

Darbības rādītāji

80 PLUS sertifikācija *	80 PLUS Gold
Mērķis, rezultāts *	PC (dators)
Strāvas padeves bloka (PSU) formas faktors *	ATX
ATX versija	3.1
EPS versija	2.92
Dzesētāja ass tips	HYB

Dizains

Produkta krāsa	Meln
Dzesēšanas tips	Aktīvs
Ventilatora diametrs	12 cm
Ventilatoru skaits	1 ventilators/ ventilatori
Ventilatora novietojums	Galvas

Iepakojuma saturs

Pievienoti kabeli	Centrālais procesors, Peripheral (Molex), SATA
-------------------	--

Svars&dimensijas	
------------------	--

Platums	150 mm
Dziļums	140 mm
Augstums	86 mm



4713224529597

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.