

TP-Link INSIGHT S345 Bullet IP security camera Outdoor 2688 x 1520 pixels Wall



Brand : TP-Link

Product code: INSIGHT S345(6MM)

Product name : INSIGHT S345

- 4MP Super-High Definition and 24h Full-Color
- People & Vehicle Analytics\$
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Active Defense and Two-Way Audio
- IP67 Waterproof
- H.265+ Compression Technology

VIGI 4MP Outdoor Full-Color Bullet Network Camera, 1/2.7", 1/3 to 1/10000 s, F1.6, 2688 x 1520, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC $\pm$ 5%, Max. 9.7 W, 5.5 mm Coaxial Power Plug, PoE: 802.3af/at, class 0, Max. 10.7 W, IP67, 184 x 74 x 74 mm, 0.525 kg, White

TP-Link INSIGHT S345. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Wall, Product colour: White, Form factor: Bullet. Lens viewing angle, horizontal: 52,7°, Lens viewing angle, vertical: 29°, Lens viewing angle, diagonal: 60,8°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 120 m, Observe distance: 50 m, Recognize distance: 24 m

Performance		Audio	
Type *	IP security camera	Audio output channels	1.0 channels
Placement supported *	Outdoor	Audio formats supported	G.711 A-law
Connectivity technology *	Wired	Sample rate	8 kHz
Maximum operating distance	120 m	Built-in microphone	✓
Wide Dynamic Range (WDR)	✓	Number of microphones	1
Day/night mode	✓	Audio detection	✓
Infrared (IR) cut-off filter	✓	Bit rate range	0 - 64 Kbit/s
Remote viewing	✓	Network	
Dynamic range	120 dB	Ethernet LAN *	✓
Design		Networking standards	IEEE 802.3af, IEEE 802.3at
Form factor *	Bullet	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Mounting type *	Wall		
Product colour *	White	Wi-Fi *	✗
Housing material	Metal	Bluetooth *	✗
Protection features	Waterproof	Live view	✓
International Protection (IP) code	IP67	Storage	
Weatherproof	✓	Compatible memory cards	MicroSD (TransFlash)
Camera		Maximum memory card size	512 GB
Minimum illumination	0 lx	Ports & interfaces	
Lens viewing angle, horizontal	52,7°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, vertical	29°	Security	
Lens viewing angle, diagonal	60,8°	Built-in siren	✓
Tilt angle range	0 - 90°	Password protection	✓
Camera shutter speed	1/3 to 1/10000	Video motion detection	✓
Image sensor		IP address filtering	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	HTTPS encryption	✓
Progressive scan	✓	Alert notification type	Push notification
Sensor type *	CMOS	Motion sensor	✓
Lens system		Mirror	✓
Detect distance	120 m		
Observe distance	50 m		
Recognize distance	24 m		

Lens system		Security	
Maximum aperture number	1.6	Human and vehicle targets classification	✓
Identify distance	12 m	Management features	
Fixed focal length	6 mm	Web-based management	✓
Night vision		Web browser	✓
Night vision *	✓	Cloud-managed *	✓
LED type	IR/White	Reset button	✓
Video		Power	
Maximum resolution *	2688 x 1520 pixels	Power source type *	DC, PoE
Total megapixels *	4 MP	Power consumption (Power over Ethernet (PoE))	10.7 W
Video compression formats	H.264, H.264+, H.265, H.265+	DC output voltage	12
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520	Operational conditions	
Video recording	✓	Operating temperature (T-T)	-30 - 60 °C
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Storage temperature (T-T)	-40 - 60 °C
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Operating relative humidity (H-H)	0 - 95%
Bit rate	Main Stream: 256 Kbps to 6 Mbps, Sub-Stream: 64 Kbps to 512 Kbps	Storage relative humidity (H-H)	0 - 95%
Back Light Compensation (BLC)	✓	Weight & dimensions	
Highlight Compensation (HLC)	✓	Width	74 mm
Digital Wide Dynamic Range (DWDR)	✓	Height	74 mm
Audio		Length	184 mm
Built-in speaker(s)	✓	Weight	525 g
Audio system	2-way	Packaging data	
Audio input channels	1.0 channels	Package type	Box
		Packaging content	
		Number of cameras *	1
		Mounting kit	✓
		Screws included	✓
		Drilling template included	✓
		Manual	✓



8885020628081

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.