



Lindy 39365 tīkla pagarinātājs Tīkla raidītājs un uztvērējs Melns

Zīmols : Lindy

Preces kods: 39365

Modeļa nosaukums : 39365

Lindy 39365. Tips: Tīkla raidītājs un uztvērējs, Maksimālais pārskaitījums attālums: 100 m, Datu pārsūtīšanas ātrums: 480 Mbit/s. Kontakta materiāls: Fosfora bronza, Konektora kontaktu apvalks: Zelts, Savienotāja materiāls: Zelts. Produkta krāsa: Melns, Apvalka materiāls: Metāls, Sertifikācija: CE, UKCA, FCC, RoHS & REACH, CP65. Izejas spriegums: 24 V, Izejas strāva: 3,75 A, Barošanas norāde: 5.5/2.1mm DC. Platums: 180 mm, Dziļums: 95 mm, Augstums: 23 mm



Darbības rādītāji

Tips *	Tīkla raidītājs un uztvērējs
Maksimālais pārskaitījums attālums *	100 m
Datu pārsūtīšanas ātrums	480 Mbit/s
Kabeļu tipi, kas ir atbalstīti	Cat6a
Chipset (mikroshēmojums) (raidītājs)	VS6320
Plug and Play	✓

Savienojamība

Ethernet LAN (RJ-45) pieslēgvietu skaits	2
RJ-45 portu skaits (raidītājs)	1
RJ-45 portu skaits (uztvērējs)	1
USB Type-C portu skaits (raidītājs)	4
USB Type-C portu skaits (uztvērējs)	2
USB 3.2 Gen 1 (3.1 Gen 1) A tipa pieslēgvietu skaits	4
DC ieejas līgza	✓
Kontakta materiāls	Fosfora bronza
Konektora kontaktu apvalks	Zelts
Savienotāja materiāls	Zelts

Dizains

Produkta krāsa *	Melns
Apvalka materiāls	Metāls
LED indikatori	✓
Sertifikācija	CE, UKCA, FCC, RoHS & REACH, CP65

Enerģijas pārvaldība

Izejas spriegums	24 V
Izejas strāva	3,75 A
Power over Ethernet (PoE)	✓
Barošanas norāde	5.5/2.1mm DC
Iekļauto strāvas kontaktdakšu veidi	AU, EU, UK, US

Ārējās vides apstākļi

Darbības temperatūras amplitūda (T-T)	0 - 40 °C
Uzglabāšanas temperatūras amplitūda (T-T)	-20 - 60 °C
Darbības relatīvā mitruma amplitūda	10 - 90%
Uzglabāšanas relatīvā mitruma amplitūda	10 - 90%

Svars&dimensijas

Platums	180 mm
Dziļums	95 mm
Augstums	23 mm
Svars	1,58 kg

Iepakojuma saturs

Pievienoti kabeli	Līdzstrāvas
Manuāls	✓

Informācija par iepakojumu

Iepakojuma tips	Kaste
Iepakojuma platums	260 mm
Iepakojuma dziļums	252 mm
Iepakojuma augstums	85 mm
Vienības apjoms	1890 cm ³

Enerģijas pārvaldība		Sertifikāti	
Ārējais jaudas adapteris	✓	Atbilstības sertifikāti	CE, Federālā komunikāciju komisija, REACH, RoHS, UKCA
Loģistiskie dati			
Harmonizētās sistēmas (HS) kods		85176990	



4002888393652

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.