

ASUS ROG STRIX B850-E GAMING WIFI AMD B850 Socket AM5 ATX**Производитель :** ASUS**Код товара:** 90MB1J60-M0AAAY0**Модель :** ROG STRIX B850-E GAMING WIFI


ASUS ROG STRIX B850-E GAMING WIFI. Производитель процессора: AMD, Сокет процессора: Socket AM5, Совместимые серии процессоров: AMD Ryzen 7000 Series, AMD Ryzen 8000 Series, AMD Ryzen 9000 Series. Поддерживаемые типы памяти: DDR5-SDRAM, Максимальная внутренняя память: 256 GB, Тип слотов памяти: DIMM. Поддерживаемые интерфейсы носителя: M.2, SATA III, Поддерживаемые типы накопителей: HDD & SSD, Уровни RAID: 0, 1, 5, 10. Максимальное разрешение: 7680 x 4320 пикселей. Тип Ethernet интерфейса: 5 Gigabit Ethernet, Основной стандарт Wi-Fi: Wi-Fi 7 (802.11be), Wi-Fi стандартов: Wi-Fi 7 (802.11be)



Процессор		Сеть	
Производитель процессора *	AMD	Тип Ethernet интерфейса	5 Gigabit Ethernet
Сокет процессора *	Socket AM5	Wi-Fi *	✓
Совместимые серии процессоров *	AMD Ryzen 7000 Series, AMD Ryzen 8000 Series, AMD Ryzen 9000 Series	Основной стандарт Wi-Fi	Wi-Fi 7 (802.11be)
		Wi-Fi стандартов	Wi-Fi 7 (802.11be)
Поддерживаемые сокеты процессоров	Socket AM5	Bluetooth	✓
		Версия Bluetooth	5.4
Память		Свойства	
Поддерживаемые типы памяти *	DDR5-SDRAM	Чипсет материнской платы *	AMD B850
Количество слотов памяти *	4	Аудио чип	Realtek ALC4080
Тип слотов памяти	DIMM	Выходные звуковые каналы *	7.1 канала
Каналы памяти	Dual-channel	Цвет товара	Черный
ECC compatibility	ECC и без ECC	Комплектующие для *	ПК
Supported memory clock speed (max)	8000 МГц	Формат материнской платы *	ATX
Максимальная внутренняя память *	256 GB	Семейство чипсета материнской платы *	AMD
Небуферизованная память	✓	Тип источника питания	ATX
Контроллеры хранения данных		Поддерживаемые операционные системы Windows	Windows 11
		Слоты расширения	
Поддерживаемые типы накопителей	HDD & SSD	Слоты PCI Express x16 (Gen 4.x)	1
Поддерживаемые интерфейсы носителя *	M.2, SATA III	Количество M.2 (M) слотов	5
		1st M.2 largest key size	2280
Количество поддерживаемых жестких дисков	4	1st M.2 highest PCI Express generation	5.0
Количество поддерживаемых дисков памяти	9	2nd M.2 largest key size	22110
Поддержка RAID	✓	2nd M.2 highest PCI Express generation	5.0
Уровни RAID	0, 1, 5, 10	3rd M.2 largest key size	2280

Графический адаптер		Слоты расширения		
Поддержка технологии параллельной обработки *	Не поддерживается	3rd M.2 highest PCI Express generation	5.0	
Максимальное разрешение	7680 x 4320 пикселей	4th M.2 largest key size	2280	
Внутренние порты		4th M.2 highest PCI Express generation	4.0	
Разъемы USB 2.0 *	2	5th M.2 largest key size	2280	
Разъемы USB 3.2 Gen 1 (3.1 Gen 1) *	1	5th M.2 highest PCI Express generation	4.0	
Разъемы USB 3.2 Gen 2 (3.1 Gen 2) *	1			
Количество разъемов SATA III *	4	BIOS		
Аудиоразъем передней панели	✓	Тип BIOS *	UEFI AMI	
Разъем передней панели	✓	Размер памяти BIOS	256 Mbit	
Разъем питания ATX (24-конт.)	✓	Кнопка сброса CMOS	✓	
Разъем вентилятора центрального процессора	✓			
Number of CPU fan connectors	2	Вес и размеры		
Количество разъемов вентилятора корпуса	5	Ширина	305 mm	
EPS разъем питания (8-конт)	✓	Глубина	244 mm	
Number of EPS power connectors (8-pin)	2			
Number of water pump connectors	1	Прочие свойства		
Number of temperature sensor headers	1	ROG SupremeFX 7.1 Surround Sound High Definition Audio CODEC ALC4080* - Impedance sense for front and rear headphone outputs - Supports: Jack-detection, Multi-streaming, Front Panel MIC Jack-retasking - High quality 120 dB SNR stereo playback output and 110 dB SNR recording input - Supports up to 32-Bit/384 kHz playback on front panel		
RGB LED контактный разъем	✓			
Number of RGB LED pin headers	3	Audio Features - SupremeFX Shielding Technology - Savitech SV3H712 AMP - Gold-plated audio jacks - Rear optical S/PDIF out port - Premium audio capacitors - Audio cover * A chassis with an HD audio module in the front panel is required to support 7.1 Surround Sound audio output. ** The LINE OUT port on the rear panel does not support spatial audio. If you wish to use spatial audio, make sure to connect your audio output device to the audio jack on the front panel of your chassis or use a USB interface audio device.		
Порты на задней панели		Выход аудио		
Количество портов USB 2.0 *	4			
Количество портов USB 3.2 Gen 2 (3.1 Gen 2) Type-A *	6			
Количество портов USB 3.2 ген 2x2 C-типа	1			
Количество портов USB4 Gen 3x2	1			
Количество портов Ethernet LAN (RJ-45) *	1			
Количество HDMI портов *	1			
Версия HDMI	2.1			
Количество портов DisplayPort	1			
Версия DisplayPort	1.4			
Линейные выходы наушников	1			
Вход линии	✓			
Порт выхода S/PDIF	✓			
Цифровой оптический аудио выход	1			
Разъем антенны WiFi-AP	2			
Сеть				
Подключение Ethernet	✓			

Прочие свойства	Total supports 5 x M.2 slots and 4 x SATA 6Gb/s ports AMD Ryzen™ 9000 & 7000 Series Desktop Processors M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode) M.2_2 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 5.0 x4 mode)* M.2_3 slot (Key M), type 2280 (supports PCIe 5.0 x4 mode)* AMD Ryzen™ 8000 Series Desktop Processors M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) M.2_2 slot (Key M), type 2242/2260/2280/22110 (Not supports)** M.2_3 slot (Key M), type 2280 (Not supports)***
Особые свойства	AMD B850 Chipset M.2_4 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode)*** M.2_5 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode) ASMedia ASM1061 Controller 4 x SATA 6Gb/s ports * When either M.2_2 or M.2_3 slot is operating, PCIeX16_1 will run x8. ** M.2_2 and M.2_3 slot will be disabled while using the AMD Ryzen™ 8000 Series Desktop Processors. *** M.2_4 slot shares bandwidth with PCIeX16(G4). When PCIeX16(G4) slot is operating, M.2_4 will be disabled.
Другие особенности	AMD RAIDXpert2 Technology for NVMe M.2 Device only Ryzen™ 9000 Series Processors: RAID 0/1/5/10 Ryzen™ 8000 Series Processors: RAID 0/1 Ryzen™ 7000 Series Processors: RAID 0/1/10 4 x DIMM slots, max. 256GB, DDR5 Supports up to 8000+MT/s (OC) with Ryzen™ 9000 & 8000 & 7000 Series Processors, ECC and Non-ECC, Un-buffered DIMM* Dual channel memory architecture Supports AMD Extended Profiles for Overclocking (EXPO™) ASUS Enhanced Memory Profile (AEMP) * Supported memory types, data rate (speed), and number of DRAM modules vary depending on the CPU and memory configuration, for more information please refer to CPU/Memory Support list under the Support tab of product information site or visit https://www.asus.com/support/download-center/. **Non-ECC, un-buffered DDR5 memory supports On-Die ECC function.
Графический выход	1 x DisplayPort* 1 x HDMI™ port** 1 x USB4® (40Gbps) port supports USB Type-C® display outputs*** - Graphics specifications may vary between CPU types. Please refer to AMD CPU specifications. * Supports max. 8K@30Hz as specified in DisplayPort 1.4 ** Supports 4K@60Hz as specified in HDMI 2.1 *** Supports max. 4K@60Hz from ASMedia ASM4241 controller as specified in DisplayPort 1.4a ***** VGA resolution support depends on processors' or graphic cards' resolution.



4711387769300



0197105769304



197105769304

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.