



Canon EOS R6 Mark III MILC Body 32.5 MP CMOS 6960 x 4640 pixels Black

Brand : Canon

Product family: EOS

Product code: 7084C004

Product name : R6 Mark III

- 32.5 megapixel resolution
- 8.5-stop IS
- Up to 7K RAW video
- 40 frames per second
- Wi-Fi** and Bluetooth
- Open Gate
- Dual Pixel CMOS AF II
- CFexpress and UHS-II SD card slots

EOS R6 Mark III

Canon EOS R6 Mark III. Camera type: MILC Body, Megapixel (approx.): 32.5 MP, Sensor type: CMOS, Maximum image resolution: 6960 x 4640 pixels. ISO sensitivity (max): 102400. Fastest camera shutter speed: 1/16000 s. Wi-Fi. HD type: 7K Ultra HD, Maximum video resolution: 6960 x 3672 pixels. Display diagonal: 7.62 cm (3"), Touchscreen. Viewfinder type: Electronic. Weight: 609 g. Product colour: Black



Picture quality		Viewfinder	
Image sensor aspect ratio	3:2	Depth of field preview	✓
Camera type *	MILC Body	Viewfinder resolution (approx.)	3690000 pixels
Megapixel (approx.) *	32.5 MP	Ports & interfaces	
Sensor type *	CMOS	PictBridge *	✗
Sensor cleaning system	EOS integrated	USB version *	3.2 Gen 2 (3.1 Gen 2)
Maximum image resolution *	6960 x 4640 pixels	USB connector	USB Type-C
Sensor cleaning system name	EOS Integrated Cleaning System	HDMI *	✓
Still image resolution(s) *	6960 x 4640, 4800 x 3200, 3472 x 2320, 2400 x 1600, 4320 x 2880, 6160 x 4640, 4256 x 3200, 3072 x 2320, 2112 x 1600, 6960 x 3904, 4800 x 2688, 3472 x 1952, 2400 x 1344, 3200 x 3200, 2320 x 2320, 1600 x 1600	HDMI connector type	Full-size
		Microphone in	✓
		Headphone outputs	1
		Network	
Supported aspect ratios	1:1, 2:3, 3:2, 3:4, 4:3, 16:9	Bluetooth *	✓
Total megapixels	34.2 MP	Bluetooth version	5.1
Image sensor size (W x H)	35.9 x 23.9 mm	Wi-Fi *	✓
Built-in low-pass filter	✓	Wi-Fi standards	Wi-Fi 5 (802.11ac)
Colour filter type	Primary colour filter	Camera	
Sensor shift IS	✓	White balance *	Cloudy, Custom modes, Daylight, Shade, Tungsten
Sensor shift IS number of stops (max)	8.5	White balance compensation (Blue/Amber)	±9
Image formats supported *	HEIF, JPEG, Raw	White balance compensation (Magenta/Green)	±9
Lens system		Custom white balance	✓
Lens mount interface	Canon RF	Number of custom white balance settings	4
Focusing		Scene modes *	Children, Close-up (macro), Food, Group photo, HDR backlight control, Handheld night scene, Landscape, Night portrait, Panning, Panorama, Portrait, Silent shutter, Smooth skin, Sports
Focus *	TTL		
Focus adjustment *	Auto/Manual		
Focusing system	Dual Pixel CMOS AF II	Shooting modes *	Intelligent auto, Manual, Scene
Auto focusing (AF) modes *	AI Focus, One Shot Focus, Servo Auto Focus		
Auto Focus (AF) object detection	Bird, Body, CAT, Dog, Eye, Face, Head, Horse, People, Train, Vehicle	Self-timer delay *	2,10 s
Face tracking	✓		
Auto Focus (AF) points	4		

Focusing		Camera	
Auto Focus (AF) points selection	Auto	Playback zoom (max)	10x
Auto Focus (AF) points manual selection	AF point expansion 4 points, AF point expansion surrounding, Flexible zone AF 1-3	Histogram	✓
Auto Focus (AF) lock	✓	Live view	✓
Auto Focus (AF) assist beam	✓	High Dynamic Range (HDR) video processing	✓
Auto Focus (AF) working range	EV -6.5 – 21	HEIF to JPEG conversion	✓
Exposure		Camera drive modes	Continuous high, Continuous high+, Continuous low, Self-timer
ISO sensitivity (min) *	100	File numbering options	Auto-reset, Consecutive numbering, Manual reset
ISO sensitivity (max) *	102400	Number of file naming user presets	2
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE	Histogram options	Brightness, RGB
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)	Highlight alert	✓
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot	Erase options	Select range
Auto Exposure (AE) lock	✓	Firmware upgradeable	✓
Number of measurement zones	384	Tripod mounting supported *	✓
Exposure bracketing (AEB)	± 3EV (1/2EV; 1/3EV stop)	Built-in processor	✓
Anti-flicker shooting	✓	Image processor	DIGIC X
Shutter		Windows operating systems supported	Windows 11
Fastest camera shutter speed *	1/16000 s	Mac operating systems supported	Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Slowest camera shutter speed *	30 s	Design	
Camera shutter type	Electronic	Market segment *	Professional
Shutter release type	Electromagnetic	Product colour *	Black
Flash		Dustproof	✓
Flash modes *	Auto, Manual	Waterproof	✓
Flash exposure lock	✓	Material	Magnesium
Flash exposure compensation	✓	Battery	
Flash exposure correction	±3EV (1/3 EV step)	Battery technology *	Lithium-Ion (Li-Ion)
Shoe mounting point	✓	Battery life (display)	620 shots
Shoe mounting point type	Hot shoe	Battery life (viewfinder)	390 shots
Flash exposure bracketing	✓	Battery type	LP-E6P
Video		Battery level indicator	✓
Video recording *	✓	Battery level indicator number of levels	6
Maximum video resolution *	6960 x 3672 pixels	Power	
HD type *	7K Ultra HD	USB Type-C charging port *	✓
Video resolutions	1920 x 1080, 2048 x 1080, 3840 x 2160, 4096 x 2160	Operational conditions	
Video formats supported	H.265, MP4	Operating temperature (T-T)	0 - 40 °C
Dual card video recording	✓	Weight & dimensions	
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit	Width	138.4 mm
Audio		Depth	88.4 mm
Built-in microphone *	✓	Height	98.4 mm
Built-in speaker(s)	✓	Weight	609 g
Memory		Packaging data	
Compatible memory cards *	CFexpress 2.0 Type B, SD, SDHC, SDXC	Quantity per pack	1 pc(s)
Memory slots	2	Package width	225 mm
Maximum memory card size	8 TB	Package depth	282 mm
Display		Package height	125 mm
Display *	LCD	Package weight	1.49 kg
Touchscreen *	✓	Packaging content	
Display diagonal *	7.62 cm (3")	Hand strap	✓
Display resolution	160000 dot	Power cord included	✓
Viewing angle, horizontal	170°	AC adapter included *	✓
Viewing angle, vertical	170°	Battery charger included	✓

Display		Packaging content	
Anti-smudge coating	✓	Batteries included	✓
Display brightness adjustment	✓	Logistics data	
Number of manual brightness adjustment levels	4		
Viewfinder		Pallet gross length	120 cm
Viewfinder type	Electronic	Pallet gross width	80 cm
Magnification	0.76x	Pallet gross height	110.5 cm
Viewfinder screen size	0.5"	Products per pallet layer	24 pc(s)
Viewfinder eyepoint (approx.)	2.3 cm	Pallet gross weight	137.9 kg
Viewfinder frame rate (smooth mode)	120 fps	Layers per pallet	3 pc(s)
Viewfinder information	AE lock, AEB, AF method, AF operation, AF point information, Anti-flicker shooting, Aperture, Auto Lighting Optimizer, Battery level, Bluetooth function, Digital Lens Optimizer, Drive mode, Electronic level, Exposure compensation, Exposure level indicator, Exposure simulation, FE lock, FEB, Flash-ready, Focus distance scale, HDR shooting, High-speed sync, Highlight tone priority, Histogram, ISO speed, Image Quality, Maximum burst, Metering mode, Multi-function lock warning, Multiple-exposure shooting, Number of self-timer shooting, Shooting mode, Shutter speed, Still photo cropping, Vertical exposure scale, White balance, Wi-Fi function	Products per pallet	72 pc(s)
		Master (outer) case width	400 mm
		Master (outer) case length	475 mm
		Master (outer) case height	325 mm
		Master (outer) case gross weight	10.2 kg
		Products per master (outer) case	6 pc(s)



4549292246292

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.