

iivama ProLite XB2493HSU-B1 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LED Black

Brand : iivama

Product family: ProLite

Product code: XB2493HSU-B1

Product name : XB2493HSU-B1



Eco-conscious 24" IPS monitor with ergonomic stand for modern workplaces

iivama ProLite XB2493HSU-B1. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Display surface: Matt, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 2.0. VESA mounting, Height adjustment. Product colour: Black

Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Cable lock slot type	Kensington
Display resolution *	1920 x 1080 pixels	Height adjustment *	✓
HD type *	Full HD	Adjustable height (max)	15 cm
Native aspect ratio *	16:9	Pivot	✓
Display technology *	LED	Pivot angle	0 - 90°
Panel type *	IPS	Swivelling	✓
Touchscreen *	✗	Swivel angle range	-60 - 60°
Display brightness (typical)	350 cd/m²	Tilt adjustment	✓
Response time *	1 ms	Tilt angle range	5 - 23°
Response time (MPRT)	1 ms	On Screen Display (OSD)	✓
Display surface	Matt	On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian, Ukrainian
Screen shape *	Flat		
Contrast ratio (typical) *	1500:1	Power	
Contrast ratio (dynamic)	80000000:1	Energy efficiency class (SDR) *	C
Maximum refresh rate *	120 Hz	Energy efficiency class (HDR) *	Not available
Viewing angle, horizontal	178°	Energy consumption (SDR) per 1000 hours *	12 kWh
Viewing angle, vertical	178°	Power consumption (typical) *	12 W
Display number of colours *	16.7 million colours	Power consumption (standby) *	12 W
Pixel pitch	0.275 x 0.275 mm	Power consumption (off)	0.3 W
Horizontal scan range	30 - 140 kHz	AC input voltage	100 - 250 V
Viewable size, horizontal	52.7 cm	AC input frequency	50/60 Hz
Viewable size, vertical	29.6 cm	Power supply type	Internal
Display diagonal (metric)	60.5 cm	Energy efficiency scale	A to G
Colour gamut standard	NTSC, sRGB	Weight & dimensions	
sRGB coverage (typical)	96%	Width (with stand)	539 mm
NTSC coverage (typical)	72%	Depth (with stand)	221.5 mm
Performance		Height (with stand)	497 mm
AMD FreeSync *	✓		
VESA Adaptive Sync support	✓		

Performance		Weight & dimensions	
Flicker-free technology	✓	Weight (with stand)	5 kg
Low Blue Light technology	✓	Height (without stand)	374 mm
Multimedia		Packaging data	
Number of speakers	2	Package width	685 mm
RMS rated power	4 W	Package depth	126 mm
Built-in speaker(s) *	✓	Package height	395 mm
Design		Package weight	6.8 kg
Market positioning *	Business	Package type	Box
Product colour *	Black	USB cable length	1.5 m
Ports & interfaces		Packaging content	
Built-in USB hub *	✓	Cables included	AC, USB, HDMI
USB hub version	2.0	HDMI cable length	1.5 m
Number of downstream ports	2	Power cable length	1.8 m
HDMI *	✓	Sustainability	
HDMI ports quantity	1	Sustainability certificates	ErP, TCO
HDMI version	1.4	Other features	
DisplayPorts quantity	1	picture adjust (brightness, contrast, ECO, ACR, OD, motion blur reduction, Adaptive Sync), colour settings (i-Style colour, blue light reducer, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time, OSD background, DDC/CI control, display information), language, extra1 (sharpness, video mode adjust, opening logo, power LED), extra 2 (shortcut key, FW version), input select, audio settings (volume, mute audio), reset (reset all)	
DisplayPort version	1.2		
Headphone out *	✓		
HDCP	✓		
Ergonomics			
VESA mounting *	✓	User controls	
Panel mounting interface	100 x 100 mm		
Cable management	✓		
Cable lock slot *	✓		
		Packaging content	quick start guide, safety guide
		Weight	5 kg
		Width	539 mm
		Depth	221.5 mm
		Control panel	Joystick: Centre: Power/Menu, Up/Signal Select, Down, Left/Submenu, Right/Volume
		Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
		Technical details	
		Native refresh rate	60 Hz



4948570126620

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.