

Chieftec ELP-700S блок питания 700 W 20+4 pin ATX PS/2 Черный

Производитель : Chieftec

Код товара: ELP-700S

Модель : ELP-700S



Chieftec ELP-700S. Общая мощность: 700 W, Входящее напряжение сети: 200 - 240 V, Частота входящего переменного тока: 47 - 63 Hz. Разъем питания материнской платы: 20+4 pin ATX, Длина кабеля питания материнской платы: 65 см, Длина кабеля питания SATA: 150,500 mm. Предназначение: ПК, Форм-фактор блока питания (БП): PS/2, 80 PLUS сертификация: 80 PLUS Bronze. Цвет товара: Черный, Тип охлаждения: Активный, Диаметр вентилятора: 12 см. Compliance certificates: CB, CE, EAC, RoHS

Энергопитание		Порты и интерфейсы	
Общая мощность *	700 W	Длина кабеля питания материнской платы	65 cm
Входящее напряжение сети *	200 - 240 V	Количество разъемов питания SATA	6
Частота входящего переменного тока	47 - 63 Hz	Длина кабеля питания SATA	150,500 mm
Ток на входе	5 A	Силовой коннектор EPS (4+4)	✓
Коэффициент мощности	0,9	Количество 6+2 контактных разъемов для питания PCI Express	1
Тип коррекции коэффициента мощности (PFC)	Активный	Порт для флоппи-дискового	✓
Комбинированная мощность (+3,3 V)	130 W	Разъем PCI Express	✓
Комбинированная мощность (+12 V)	648 W	Тип свивки	Немодульный
Комбинированная мощность (+5 V)	130 W	Производительность	
Комбинированная мощность (-12 V)	3,6 W	80 PLUS сертификация *	80 PLUS Bronze
Комбинированная мощность (+5 VSB)	12,5 W	Поддерживаемые форм-факторы материнской платы	ATX
Максимальный выходной ток (+3.3 V)	22 A	Предназначение *	ПК
Максимальный выходной ток (+12 V)	54 A	Форм-фактор блока питания (БП) *	PS/2
Максимальный выходной ток (+5 V)	22 A	Версия ATX	2.3
Максимальный выходной ток (+5 VSB)	2,5 A	Дизайн	
Эффективность	85%	Цвет товара	Черный
Функции защиты электропитания	Защита от перегрузки,	Тип охлаждения	Активный
	Перенапряжение, Короткое замыкание, Пониженное напряжение	Диаметр вентилятора	12 cm
Порты и интерфейсы		Количество вентиляторов	1 вентилятор(ы)
Разъем питания материнской платы *	20+4 pin ATX	Вкл/Выкл переключатель	✓
		Сертификаты	
		Compliance certificates	CB, CE, EAC, RoHS
		Вес и размеры	
		Ширина	140 mm
		Глубина	150 mm
		Высота	86 mm
		Вес	1,65 kg
		Данные об упаковке	
		Масса брутто	1,9 kg
		Тип упаковки	Коробочная версия



4710713230972

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.