



## Canon Wide-Angle RF 24 mm F1.8 Macro IS STM Camera Lenses, Black

**Brand :** Canon

**Product code:** 5668C005

**Product name :** Wide-Angle RF 24 mm F1.8 Macro IS STM Camera Lenses, Black



- A dedicated prime lens for landscape enthusiasts looking for less distortion and higher quality images
- A 9-blade circular aperture allows you to shoot in low light
- Offers 5-stops of protection against blur from camera shake
- Smooth and quiet focusing with speed and accuracy; perfect for stills as well as video
- Ideal for travel where space in a bag is limited

Wide-Angle RF 24 mm F1.8 Macro IS STM Camera Lenses, Black

Canon Wide-Angle RF 24 mm F1.8 Macro IS STM Camera Lenses, Black. Component for: MILC, Lens structure (elements/groups): 11/9, Lens type: Wide zoom lens. Camera brands compatibility: Canon, AF actuator: STM, Lens colour: Black. Product colour: Black, Mounting type: Bayonet. Country of origin: Japan, Products per master (outer) case: 6 pc(s), Master (outer) case gross weight: 3.34 kg. Diameter: 7.44 cm, Filter size: 52 mm, Length: 63.1 mm



| Lens system                                   |                                   | Design                                |           |
|-----------------------------------------------|-----------------------------------|---------------------------------------|-----------|
| Component for *                               | MILC                              | Product colour                        | Black     |
| Lens type *                                   | Wide zoom lens                    | Mounting type                         | Bayonet   |
| Lens structure (elements/groups) *            | 11/9                              | Dustproof                             | ✗         |
| Lens viewing angle, horizontal                | 74°                               | Weatherproof                          | ✗         |
| Focus adjustment                              | Auto/Manual                       | Logistics data                        |           |
| Lens viewing angle, vertical                  | 53°                               | Country of origin                     | Japan     |
| Fixed focal length                            | 24 mm                             | Products per master (outer) case      | 6 pc(s)   |
| Lens viewing angle, diagonal                  | 84°                               | Master (outer) case gross weight      | 3.34 kg   |
| Focal length range                            | 24 - 24 mm                        | Master (outer) case length            | 386 mm    |
| Minimum aperture number *                     | 22                                | Master (outer) case width             | 263 mm    |
| Number of diaphragm blades                    | 9                                 | Master (outer) case height            | 237 mm    |
| Closest focusing distance *                   | 0.14 m                            | Products per pallet                   | 180 pc(s) |
| Maximum aperture number *                     | 1.8                               | Pallet gross length                   | 120 cm    |
| Macro ratio                                   | 1:2                               | Pallet gross width                    | 80 cm     |
| Number of aspheric elements                   | 1                                 | Pallet gross height                   | 131.5 cm  |
| Zoom capability *                             | ✓                                 | Quantity per pack                     | 1 pc(s)   |
| Image sensor format                           | Full frame                        | Pallet gross weight                   | 118.8 kg  |
| Lens mount interface *                        | Canon RF                          | Layers per pallet                     | 5 pc(s)   |
| Teleconverter/Extender compatible             | ✗                                 | Master (outer) cases per pallet layer | 6 pc(s)   |
| Control ring                                  | ✓                                 | Products per pallet layer             | 36 pc(s)  |
| Image stabilizer                              | ✓                                 | Weight & dimensions                   |           |
| Image stabilizer type                         | Optical Image Stabilization (OIS) | Length                                | 63.1 mm   |
| Image stabilizer number of stops (OIS)        | 5                                 | Weight                                | 270 g     |
| Image stabilizer number of stops (IBIS x OIS) | 6.5                               | Diameter *                            | 7.44 cm   |
|                                               |                                   | Filter size *                         | 52 mm     |
| Performance                                   |                                   | Packaging data                        |           |
| Auto focus                                    | ✓                                 | Package width                         | 150 mm    |
| Manual focus                                  | ✓                                 | Package depth                         | 150 mm    |

| Performance                                  |                             | Packaging data         |          |
|----------------------------------------------|-----------------------------|------------------------|----------|
| AF actuator                                  | STM                         | Package height         | 150 mm   |
| Lens colour                                  | Black                       | Package weight         | 350 g    |
| Camera brands compatibility *                | Canon                       | Package volume         | 2723 cm³ |
| Circular aperture                            | ✓                           | Packaging content      |          |
| Lens coating features                        | Super Spectra Coating (SSC) | Lens cap included      | ✓        |
| Number of Ultra-low Dispersion (UD) elements | 1                           | Lens cap model         | E-52 II  |
| Lens hood                                    | ✓                           | Rear lens cap included | ✓        |
| Lens hood model                              | EW-65B                      | Rear lens cap model    | RF       |
|                                              |                             | User guide             | ✓        |



4549292207309

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.