



TP-Link Omada EAP650-Outdoor 3000 Mbit/s Balts Power over Ethernet (PoE)

Zīmols : TP-Link

Preču ģimene: Omada

Preces kods: EAP650-OUTDOOR

Modeļa nosaukums : EAP650-Outdoor

TP-Link Omada EAP650-Outdoor. 2.4 GHz, 5 GHz, Maksimālais datu pārraides ātrums: 3000 Mbit/s. Drošības algoritma atbalsts: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise. Ethernet LAN datu pārsūtīšanas ātrums: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produkta krāsa: Balts



Īpašības		Savienojamība	
2.4 GHz *	✓	Ethernet LAN (RJ-45) pieslēgvietu skaits *	1
5 GHz *	✓	Enerģijas pārvaldība	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maksimālais datu pārraides ātrums *	3000 Mbit/s	Dizains	
Maksimālais datu pārraides ātrums (2,4 GHz)	574 Mbit/s	Izvietošana *	Statīvs, Siena
Maksimālais datu pārraides ātrums (5 GHz)	2402 Mbit/s	Produkta krāsa *	Balts
Ethernet LAN datu pārsūtīšanas ātrums	10,100,1000 Mbit/s	International Protection (IP) code	IP67
Tīkla standarts	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at	Atiestates poga	✓
		LED indikatori	✓
Kabeļa likšanas tehnoloģija		Antena	
Lietotāju skaits	250 lietotājs(i)	Antenas tips *	Iekšējs
Automātiska kanāla atlase	✓	Antenas virziena veids	Omni-directional
Automātiskā kanālu skenēšana	✓	Sertifikāti	
MIMO	✓	Sertifikācija	CE, FCC, RoHS
MIMO veids	Multi User MIMO	Svars&dimensijas	
Fit AP režīma funkcijas	Šūnu tīklošana	Platums	280,4 mm
Atbalsta VLAN	✓	Dziļums	106,5 mm
Ātruma limitēšana	✓	Augstums	56,8 mm
Joslas virzīšana	✓	Iepakojuma saturs	
Airtime Fairness (ATF)	✓	Skaits iepakojumā	1 pcs
Quality of Service (QoS) atbalsts	✓	Montāžas komplekts	✓
BeamForming	✓	Ātrās startēšanas gids	✓

Drošība		Ārējās vides apstākļi	
Drošības algoritma atbalstīts *	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise	Darbības relatīvā mitruma amplitūda	10 - 90%
MAC adreses filtrēšana	✓	Darbības temperatūras amplitūda (T-T)	-30 - 70 °C
Service Set Identifier (SSID) funkcijas	Multiple SSIDs, SSID pārraides ieslēgšana/izslēgšana	Uzglabāšanas temperatūras amplitūda (T-T)	-40 - 70 °C
		Uzglabāšanas relatīvā mitruma amplitūda	5 - 90%



4897098682098



4897098683552



0840030703553



840030703553

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.