



Dahua Technology WizSense IPC-HDW1439V-A-IL Dome IP security camera 2560 x 1440 pixels Ceiling/Wall/Pole

Brand : Dahua Technology

Product family: WizSense

Product code: IPC-HDW1439V-A-IL-0280B-B

Product name : IPC-HDW1439V-A-IL

- 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image
 - Outputs max. 4 MP (2560 × 1440)@25/30 fps
 - H.265 codec, high compression rate, ultra-low bit rate
 - Built-in IR LED and warm light, the max. IR illumination distance is 30 m and warm light distance is 30 m
 - WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
 - ROI, SMART H.264 +/-H.265+, flexible coding, applicable to various bandwidth and storage environments
 - Abnormality detection: Motion detection, video tampering, audio detection, network disconnection, IP conflict and illegal access
 - Built in Mic
 - 12 VDC/PoE power supply, easy for installation
 - IP67 protection
 - Supports human and vehicle detection
- 1/2.9" CMOS, 2560 (H) × 1440 (V), 128 MB, >56 dB, M12, F1.6, 0°/180°

Dahua Technology WizSense IPC-HDW1439V-A-IL Dome IP security camera 2560 x 1440 pixels Ceiling/Wall/Pole:

4MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera

Performance		Video	
Type *	IP security camera	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Connectivity technology *	Wired	Back Light Compensation (BLC)	✓
Wide Dynamic Range (WDR)	✓	Highlight Compensation (HLC)	✓
Day/night mode	✓	Region of Interest (ROI) encoding	✓
Infrared (IR) cut-off filter	✓	Audio	
Certification	CE-LVD: EN 62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU	Audio formats supported	G.711 A-law, G.711 μ-law, G.726, PCM
Design		Signal-to-Noise Ratio (SNR)	56 dB
Form factor *	Dome	Network	
Mounting type *	Ceiling/Wall/Pole	Ethernet LAN *	✓
Product colour *	Black	Ethernet interface type	Fast Ethernet
Housing material	Metal, Plastic	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multidifusión; ICMP; IGMP; P2P
Protection features	Dust resistant	Quality of Service (QoS) support	✓
International Protection (IP) code	IP67	Streaming method	Multicast
Camera		Storage	
Minimum illumination	0.0006 lx	Internal memory	128 MB
Angle of rotation	360°	ROM capacity	128 MB
Lens viewing angle, horizontal	94°	Ports & interfaces	
Lens viewing angle, vertical	52°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, diagonal	111°	Security	
Tilt angle range	0 - 78°	Video motion detection	✓
Pan range	0 - 360°	Active tampering alarm	✓
White balance	Auto, Manual, Natural, Outdoor, Regional custom		
Camera shutter type	Electronic		
Camera shutter speed	1/3 -1/100000		
Image sensor			
Number of sensors	1		

Image sensor		Management features	
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Web browser	✓
Progressive scan	✓	Management software	PSS inteligente Lite; DSS; DMSS
Sensor type *	CMOS	Power	
Night vision		Power source type *	DC, PoE
Night vision *	✓	Power consumption (typical)	2 W
Night vision distance	30 m	DC output voltage	12
LED type	IR	Operational conditions	
Video		Operating temperature (T-T)	-40 - 60 °C
Maximum resolution *	2560 x 1440 pixels	Storage temperature (T-T)	-40 - 60 °C
Total megapixels *	4 MP	Operating relative humidity (H-H)	0 - 95%
Video formats supported	H.264, H.265	System requirements	
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265, H.265+	Mobile operating systems supported	Android, iOS
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440	Weight & dimensions	
		Width	100.9 mm
Video streaming	✓	Diameter	11 cm
Gain control type	Auto/Manual	Weight	330 g
Flip & mirror	✓	Packaging data	
Privacy masking	✓	Package weight	450 g
		Packaging content	
		Number of cameras *	1



6923172570352

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.