



Lindy 1m Cat.6A U/UTP LSZH Cable, Grey

Brand : Lindy **Product code:** 47613

Product name : 1m Cat.6A U/UTP LSZH Cable, Grey

1m Cat.6A U/UTP LSZH Cable, Grey

Lindy 1m Cat.6A U/UTP LSZH Cable, Grey:

Cat.6A U/UTP LSZH network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10GBase-T.

Cat.6A cable for operating frequencies up to 500MHz. The unshielded version (U/UTP) can be used for Gigabit Ethernet thanks to the special design of the electrophysical parameters (NExT, FExT, etc.) despite the lack of shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m, 15m



Features		Operational conditions	
Product colour *	Grey	Storage temperature (T-T)	-20 - 75 °C
Cable length *	1 m	Sustainability	
Cable standard *	Cat6a	Doesn't contain	Halogen
Cable shielding *	U/UTP (UTP)	Certificates	
Connector 1 *	RJ-45	Compliance certificates	REACH, RoHS, UL
Connector 2 *	RJ-45	Certification	RoHS, REACH, UL, California Proposition 65
Connector 1 gender *	Male	Weight & dimensions	
Connector 2 gender *	Male	Width	11.6 mm
Connector 1 form factor	Straight	Depth	22.8 mm
Connector 2 form factor	Straight	Height	8.3 mm
Connector contacts plating	Gold	Outer diameter	5.8 mm
Connector shielding	✓	Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Connector shield material	Aluminium	Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Jacket material	Low smoke zero halogen (LSZH)	Packaging content	
Cable shape *	Round	Quantity per pack	1 pc(s)
Conductor material	Copper	Manual	✓
Connector housing material	Polycarbonate (PC)	Packaging data	
Cabling technology	10GBase-T	Package type	Polybag
AWG wire size	26	Logistics data	
Frequency	500 MHz	Warranty period	10 year(s)
Bend radius (min)	6.9 cm	Technical details	
Operational conditions		Sustainability compliance	✓
Operating temperature (T-T)	-10 - 60 °C		



4002888476133

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.