



iiyama ProLite X2792QSU-B1 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black

Brand : iiyama

Product family: ProLite

Product code: X2792QSU-B1

Product name : X2792QSU-B1

27" IPS QHD panel with 4-side slim bezel and B energy class

iiyama ProLite X2792QSU-B1 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black:

The ProLite X2792QSU is a 27" QHD monitor ideal for professionals who need more screen space, precise image quality, and a sustainable choice. Packaged without plastic and made from 85% post-consumer recycled materials, it meets TCO Certification and EPEAT Silver standards. With a resolution of 2560 x 1440, it offers 77% more screen space than Full HD, helping you work across multiple windows and view more detail without constant scrolling. Its IPS panel delivers sharp detail, vibrant colours and wide viewing angles, while the frameless design creates a sleek, distraction-free workspace. To take care of your eye health, it complies with the Eye Safe and Eye Comfort Certifications.



Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	HDCP	✓
Display resolution *	2560 x 1440 pixels	Ergonomics	
HD type *	Quad HD	VESA mounting *	✓
Native aspect ratio *	16:9	Panel mounting interface	100 x 100 mm
Display technology *	LED	Wall mountable	✓
Panel type *	IPS	Cable management	✓
Display brightness (typical)	350 cd/m ²	Cable lock slot *	✓
Response time *	3 ms	Cable lock slot type	Kensington
Response time measurement type	GTG (Gray to Gray)	Tilt adjustment	✓
Display surface	Matt	Tilt angle range	4 - 20°
Screen shape *	Flat	On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian, Ukrainian
Contrast ratio (typical) *	1500:1	Power	
Contrast ratio (dynamic)	80000000:1	Energy efficiency class (SDR) *	B
Maximum refresh rate *	120 Hz	Energy efficiency class (HDR) *	Not available
Viewing angle, horizontal	178°	Energy consumption (SDR) per 1000 hours *	10.7 kWh
Viewing angle, vertical	178°	Power consumption (typical) *	12 W
Display number of colours *	16.7 million colours	Power consumption (standby) *	0.5 W
Pixel pitch	0.233 x 0.233 mm	Power consumption (off)	0.3 W
Horizontal scan range	30 - 140 kHz	AC input voltage	100 - 240 V
Viewable size, horizontal	59.7 cm	AC input frequency	50/60 Hz
Viewable size, vertical	33.6 cm	Power supply type	Internal
Display diagonal (metric)	68.6 cm	Energy efficiency scale	A to G
DDC/CI	✓	Weight & dimensions	
sRGB coverage (typical)	96%	Width (with stand)	616.5 mm
NTSC coverage (typical)	72%	Depth (with stand)	190 mm
Performance		Height (with stand)	436 mm
NVIDIA G-SYNC *	✓	Weight (with stand)	4.1 kg
NVIDIA G-SYNC type	G-SYNC		
AMD FreeSync *	✓		
VESA Adaptive Sync support	✓		
Flicker-free technology	✓		

Performance		Packaging data	
Low Blue Light technology	✓	Package weight	6.4 kg
Multimedia		USB cable length	1.8 m
Number of speakers	2	Packaging content	
RMS rated power	4 W	Cables included	AC, USB, HDMI
Built-in speaker(s) *	✓	HDMI cable length	1.8 m
Design		Power cable length	1.8 m
Market positioning *	Business	Sustainability	
Product colour *	Black	Sustainability certificates	ErP, TCO
Ports & interfaces		Other features	
Built-in USB hub *	✓	Packaging content	quick start guide, safety guide
USB hub version	3.2 Gen 1 (3.1 Gen 1)	User controls	picture adjust (brightness, contrast, ECO, ACR, OD, Adaptive Sync, X-Res Technology, DPS), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.), OSD settings (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI, display information), miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, audio settings (volume, mute), recall (recall all))
Number of downstream ports	2		
HDMI *	✓		
HDMI ports quantity	1		
HDMI version	2.0	Weight	4.1 kg
DisplayPorts quantity	1	Height	436 mm
DisplayPort version	1.2	Width	616.5 mm
Headphone out *	✓	Depth	190 mm
		Control panel	Joystick: Center: Power/Menu, Up/Input Select, Down, Left/i-Style colour/Eco/Blue Light Reducer, Right/Volume/Mute Audio
		Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
Technical details			
		Native refresh rate	60 Hz



4948570126170

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.