


NETGEAR GS105E-200PES network switch Managed L2/L3 Gigabit Ethernet (10/100/1000) Grey

Brand : NETGEAR

Product code: GS105E-200PES

Product name : GS105E-200PES

GS105E-200PES - 5x RJ-45, 270 g, 10/100/1000 Mbps  
NETGEAR GS105E-200PES. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex. MAC address table: 8000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3i, IEEE 802.3u, IEEE...



| Management features                             |                                                                                                         | Multicast features                  |                                                                                                                                 |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Switch type *                                   | Managed                                                                                                 | Number of multicast groups filtered | 128                                                                                                                             |
| Switch layer                                    | L2/L3                                                                                                   | Design                              |                                                                                                                                 |
| Quality of Service (QoS) support                | ✓                                                                                                       | Stackable *                         | ✗                                                                                                                               |
| Ports & interfaces                              |                                                                                                         | Product colour                      | Grey                                                                                                                            |
| Basic switching RJ-45 Ethernet ports quantity * | 5                                                                                                       | LED indicators                      | ✓                                                                                                                               |
| Basic switching RJ-45 Ethernet ports type *     | Gigabit Ethernet (10/100/1000)                                                                          | Power over Ethernet (PoE)           |                                                                                                                                 |
| Network                                         |                                                                                                         | Power over Ethernet (PoE) *         | ✗                                                                                                                               |
| Networking standards *                          | IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x | Operational conditions              |                                                                                                                                 |
| 10G support *                                   | ✗                                                                                                       | Operating temperature (T-T)         | 0 - 50 °C                                                                                                                       |
| Copper ethernet cabling technology              | 1000BASE-T, 100BASE-T, 10BASE-T                                                                         | Storage temperature (T-T)           | -20 - 70 °C                                                                                                                     |
| Port mirroring                                  | ✓                                                                                                       | Operating relative humidity (H-H)   | 0 - 90%                                                                                                                         |
| Full duplex                                     | ✓                                                                                                       | Storage relative humidity (H-H)     | 0 - 95%                                                                                                                         |
| Flow control support                            | ✓                                                                                                       | Operating altitude                  | 0 - 3000 m                                                                                                                      |
| Broadcast storm control                         | ✓                                                                                                       | Weight & dimensions                 |                                                                                                                                 |
| VLAN support                                    | ✓                                                                                                       | Width                               | 94 mm                                                                                                                           |
| Number of VLANs                                 | 64                                                                                                      | Depth                               | 101 mm                                                                                                                          |
| Data transmission                               |                                                                                                         | Height                              | 26 mm                                                                                                                           |
| Switching capacity *                            | 10 Gbit/s                                                                                               | Weight                              | 270 g                                                                                                                           |
| MAC address table *                             | 8000 entries                                                                                            | Packaging content                   |                                                                                                                                 |
| Jumbo frames support                            | ✓                                                                                                       | Quick start guide                   | ✓                                                                                                                               |
| Security                                        |                                                                                                         | Certificates                        |                                                                                                                                 |
| DHCP features                                   | DHCP client                                                                                             | Certification                       | CE,CSA (CSA 22.2 #950) UL (UL 1950)/cUL IEC 950/EN 60950 FCC Part 15, VCCI, EN55022 (CISPR 22), C-Tick, EN50082-1, EN55024, CCC |
| IGMP snooping                                   | ✓                                                                                                       | Logistics data                      |                                                                                                                                 |
| Multicast features                              |                                                                                                         | Harmonized System (HS) code         | 85176990                                                                                                                        |
| Multicast support                               | ✓                                                                                                       |                                     |                                                                                                                                 |



0606449101522



606449101522



5054484570943



0240049101522



240049101522

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.