



## DELL PowerEdge T360 server 960 GB Tower (4.5U) Intel Xeon 6 6357P 3 GHz 64 GB DDR5-SDRAM 700 W

**Brand :** DELL

**Product family:** PowerEdge

**Product code:** 6YVRW

**Product name :** T360

- No OS
- Intel Xeon 6 6357P (24MB Cache, 3GHz)
- 64GB DDR5-SDRAM (2 x 32) & 960GB SSD
- iDRAC9, Enterprise 16G

Intel Xeon 6 6357P (24MB Cache, 3GHz), 64GB DDR5-SDRAM, 960GB SSD, LAN (Broadcom 5720), PERC H755 Adapter FH, iDRAC9, Enterprise 16G, 700W, No OS

DELL PowerEdge T360 server 960 GB Tower (4.5U) Intel Xeon 6 6357P 3 GHz 64 GB DDR5-SDRAM 700 W:

### Processing performance, GPU support

The 4.5U, single-socket PowerEdge T360 is a specially designed form factor for customers desiring versatility, affordability, and processing power.

DELL PowerEdge T360. Processor family: Intel Xeon 6, Processor frequency: 3 GHz, Processor model: 6357P. Internal memory: 64 GB, Internal memory type: DDR5-SDRAM, Memory layout (slots x size): 2 x 32 GB. Total storage capacity: 960 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 700 W. Chassis type: Tower (4.5U)



| Processor                                  |                           | Expansion slots                        |                                                                                                                                                 |
|--------------------------------------------|---------------------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Processor manufacturer *                   | Intel                     | PCI Express x4 slots                   | 2                                                                                                                                               |
| Processor family *                         | Intel Xeon 6              | Design                                 |                                                                                                                                                 |
| Processor model *                          | 6357P                     | Chassis type *                         | Tower (4.5U)                                                                                                                                    |
| Processor frequency *                      | 3 GHz                     | Product colour                         | Black                                                                                                                                           |
| Processor boost frequency                  | 5.4 GHz                   | Bezel                                  | ✓                                                                                                                                               |
| Performance cores                          | 8                         | Performance                            |                                                                                                                                                 |
| Processor cache                            | 24 MB                     | Remote administration                  | iDRAC9, Enterprise 16G                                                                                                                          |
| Number of processors installed             | 1                         | Software                               |                                                                                                                                                 |
| Thermal Design Power (TDP)                 | 80 W                      | Operating system installed *           | ✗                                                                                                                                               |
| System bus rate                            | 16 GT/s                   | Compatible operating systems *         | Canonical Ubuntu Server LTS<br>Microsoft Windows Server with<br>Hyper-V Red Hat Enterprise Linux<br>SUSE Linux Enterprise Server<br>VMware ESXi |
| Processor threads                          | 16                        |                                        |                                                                                                                                                 |
| Memory types supported by processor        | DDR5-SDRAM                | Power                                  |                                                                                                                                                 |
| Memory clock speeds supported by processor | 4800 MHz                  | Redundant power supply (RPS) support * | ✗                                                                                                                                               |
| Memory                                     |                           | Power supply *                         | 700 W                                                                                                                                           |
| Internal memory *                          | 64 GB                     | Number of main power supplies          | 1                                                                                                                                               |
| Internal memory type *                     | DDR5-SDRAM                | Power supply input voltage             | 200 - 240 V                                                                                                                                     |
| Buffered memory type                       | Unregistered (unbuffered) | Power cable length                     | 2 m                                                                                                                                             |
| Memory slots                               | 4x DIMM                   | Power cable connector 1                | C13 coupler                                                                                                                                     |
| ECC                                        | ✓                         | Power cable connector 2                | C14 coupler                                                                                                                                     |
| Memory layout (slots x size)               | 2 x 32 GB                 | Power cable current                    | 10 A                                                                                                                                            |
| Memory data transfer rate                  | 5600 MT/s                 | Operational conditions                 |                                                                                                                                                 |
| Maximum internal memory *                  | 128 GB                    | Storage temperature (T-T)              | -40 - 65 °C                                                                                                                                     |
| Storage                                    |                           | Storage relative humidity (H-H)        | 5 - 95%                                                                                                                                         |
| Total storage capacity *                   | 960 GB                    | Operating altitude                     | 0 - 2048 m                                                                                                                                      |
| Number of SSDs installed                   | 2                         |                                        |                                                                                                                                                 |
| SSD capacity                               | 480 GB                    |                                        |                                                                                                                                                 |

| Storage                                         |                      | Operational conditions                                  |                     |
|-------------------------------------------------|----------------------|---------------------------------------------------------|---------------------|
| SSD interface                                   | SATA III             | Non-operating altitude                                  | 0 - 12000 m         |
| SSD size                                        | 2.5"                 | Certificates                                            |                     |
| Supported SSD sizes                             | 3.5"                 | 80 PLUS certification                                   | 80 PLUS Titanium    |
| Number of SSDs supported                        | 8                    | Carbon footprint                                        |                     |
| RAID support *                                  | ✗                    | Total carbon footprint (kg of CO2e)                     | 1409                |
| Supported RAID controllers                      | PERC H755 Adapter FH | Total carbon emissions, standard deviation (kg of CO2e) | 1213                |
| Hot-Plug support                                | ✓                    | Carbon emissions, manufacturing (kg of CO2e)            | 295.89              |
| Optical drive type *                            | ✗                    | Carbon emissions, logistics (kg of CO2e)                | 154.99              |
| Storage drive adapter included                  | ✓                    | Carbon emissions, energy usage (kg of CO2e)             | 929.94              |
| Storage drive adapter type                      | 2.5" - 3.5"          | Carbon emissions, end-of-life (kg of CO2e)              | 28.18               |
| Network                                         |                      | PAIA version                                            | PAIA 1.4.0, 2024    |
| LAN controller                                  | Broadcom 5720        | Weight & dimensions                                     |                     |
| Ethernet LAN                                    | ✓                    | Width                                                   | 175 mm              |
| Cabling technology                              | 10/100/1000Base-T(X) | Depth                                                   | 581.1 mm            |
| Ethernet interface type                         | Gigabit Ethernet     | Other features                                          |                     |
| Ports & interfaces                              |                      | Data transfer rate                                      | 6 Gbit/s            |
| Ethernet LAN (RJ-45) ports *                    | 2                    | Bytes per sector                                        | 512                 |
| USB 2.0 ports quantity                          | 3                    | Target workload                                         | Read Intensive (RI) |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4                    |                                                         |                     |
| VGA (D-Sub) ports quantity                      | 1                    |                                                         |                     |
| Serial ports quantity                           | 1                    |                                                         |                     |
| Power cables quantity                           | 2                    |                                                         |                     |



5397184960479

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.