



APC Smart-UPS SMT3000RMI2UNC - 8x C13, 1x C19, USB, Rackmount 2U, NMC, 3000VA

Brand : APC

Product code: SMT3000RMI2UNC

Product name : APC Smart-UPS SMT3000RMI2UNC - 8x C13, 1x C19, USB, Rackmount 2U, NMC, 3000VA




APC Smart-UPS SMT3000RMI2UNC - 8x C13, 1x C19, USB, rack mountable, NMC, 3000VA
APC Smart-UPS SMT3000RMI2UNC - 8x C13, 1x C19, USB, Rackmount 2U, NMC, 3000VA. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, C20 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 547 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

Features		Design	
UPS topology *	Line-Interactive	Product colour *	Black
Output power capacity *	3 kVA	Display type	LCD
Output power *	2700 W	LED indicators	✓
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	151 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	302 V	Storage temperature (T-T)	-15 - 45 °C
Input frequency *	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (min)	220 V	Storage relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Operating altitude	0 - 3000 m
Output frequency	50/60 Hz	Non-operating altitude	0 - 15000 m
Surge energy rating	320 J	Certificates	
Response time	4 ms	Compliance certificates	RoHS
Emergency Power Off (EPO)	0	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Noise level	55 dB	Packaging content	
Surge protection	✓	Rack mount kit	✓
Audible alarm(s)	✓	Cables included	Input power cable, USB cable
Web-based management	✓	Management card included	✓
Audible alarm modes	Battery replacement	Quick installation guide	✓
Auto-restart	✓	Sustainability	
Ports & interfaces		Sustainability certificates	Green Premium
AC outlet types	C13 coupler, C19 coupler, C20 coupler	Weight & dimensions	
Power plug	C20 coupler	Width	480 mm
AC outlets quantity	9 AC outlet(s)	Depth	683 mm
USB 2.0 ports quantity	1	Height	86 mm
SmartSlot	✓	Weight	44.2 kg
SmartConnect port	✗	Packaging data	
Battery		Resource CD	✓
Battery technology	Sealed Lead Acid (VRLA)	Package width	600 mm
Battery capacity	547 Ah	Package depth	980 mm
Battery recharge time	3 h	Package height	254 mm
Hot-swap battery	✓	Package weight	51.6 kg
Automatic battery test	✓		
Cold start	✓		

Design		Logistics data	
Form factor *	Rackmount	Products per pallet	8 pc(s)
Rack capacity	2U	Harmonized System (HS) code	85078000
Cable length	2 m	Total carbon footprint (kg of CO2e)	2958.37
		Other features	
		Output voltage	230 V



0731304327707



731304327707

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.