



## APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA



**Brand :** APC

**Product code:** SMT1500RMI2UNC

**Product name :** Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA

APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA

APC Smart-UPS SMT1500RMI2UNC - 4x C13, USB, rack mountable, NMC, 1500VA. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1000 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 432 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE


| Features                        |                          | Design                              |                                                                        |
|---------------------------------|--------------------------|-------------------------------------|------------------------------------------------------------------------|
| UPS topology *                  | Line-Interactive         | Product colour *                    | Black                                                                  |
| Output power capacity *         | 1.5 kVA                  | Display type                        | LCD                                                                    |
| Output power *                  | 1000 W                   | LED indicators                      | ✓                                                                      |
| Waveform *                      | Sine                     | Operational conditions              |                                                                        |
| Input operation voltage (min) * | 151 V                    | Operating temperature (T-T)         | 0 - 40 °C                                                              |
| Input operation voltage (max) * | 302 V                    | Storage temperature (T-T)           | -15 - 45 °C                                                            |
| Input frequency *               | 50/60 Hz                 | Operating relative humidity (H-H)   | 0 - 95%                                                                |
| Output operation voltage (min)  | 220 V                    | Storage relative humidity (H-H)     | 0 - 95%                                                                |
| Output operation voltage (max)  | 240 V                    | Operating altitude                  | 0 - 3000 m                                                             |
| Output frequency                | 50/60 Hz                 | Non-operating altitude              | 0 - 15000 m                                                            |
| Output voltage regulation       | 5%                       | Certificates                        |                                                                        |
| Surge energy rating             | 459 J                    | Compliance certificates             | RoHS                                                                   |
| Response time                   | 2 ms                     | Certification                       | CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE |
| Emergency Power Off (EPO)       | 0                        | Packaging content                   |                                                                        |
| Noise level                     | 46 dB                    | Rack mount kit                      | ✓                                                                      |
| Audible alarm(s)                | ✓                        | Cables included                     | Input power cable, USB cable                                           |
| Web-based management            | ✓                        | Management card included            | ✓                                                                      |
| Audible alarm modes             | Battery replacement      | Quick installation guide            | ✓                                                                      |
| Auto-restart                    | ✓                        | Sustainability                      |                                                                        |
| Ports & interfaces              |                          | Sustainability certificates         | Green Premium                                                          |
| AC outlet types                 | C13 coupler, C14 coupler | Weight & dimensions                 |                                                                        |
| Power plug                      | C14 coupler              | Width                               | 432 mm                                                                 |
| AC outlets quantity             | 4 AC outlet(s)           | Depth                               | 457 mm                                                                 |
| USB 2.0 ports quantity          | 1                        | Height                              | 89 mm                                                                  |
| Ethernet LAN (RJ-45) ports      | 1                        | Weight                              | 28.6 kg                                                                |
| SmartSlot                       | ✓                        | Packaging data                      |                                                                        |
| SmartConnect port               | ✗                        | Resource CD                         | ✓                                                                      |
| Battery                         |                          | Package width                       | 594 mm                                                                 |
| Battery technology              | Sealed Lead Acid (VRLA)  | Package depth                       | 603 mm                                                                 |
| Battery capacity                | 432 Ah                   | Package height                      | 251 mm                                                                 |
| Battery recharge time           | 3 h                      | Package weight                      | 31.8 kg                                                                |
| Hot-swap battery                | ✓                        | Logistics data                      |                                                                        |
| Automatic battery test          | ✓                        | Products per pallet                 | 8 pc(s)                                                                |
| Cold start                      | ✓                        | Harmonized System (HS) code         | 85078000                                                               |
| Design                          |                          | Total carbon footprint (kg of CO2e) | 1407.66                                                                |
| Form factor *                   | Rackmount                |                                     |                                                                        |
| Rack capacity                   | 2U                       |                                     |                                                                        |

**Other features**

|                |       |
|----------------|-------|
| Output voltage | 230 V |
|----------------|-------|



0731304327684



731304327684

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.