

Philips V Line 271V8LAB/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips

Product family: V Line

Product code: 271V8LAB/00

Product name : 271V8LAB/00

Monitor 271V8LAB LCD monitor

Philips V Line 271V8LAB/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black:

Philips V line wide-view monitor gives viewing beyond boundaries. Adaptive Sync, a 1 ms MPRT response rate and a 100 Hz refresh rate deliver smooth video display. Features like anti-glare, LowBlue mode and flicker-free make it easy on the eyes.

Philips V Line 271V8LAB/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°, Built-in speaker(s), VESA mounting, Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	VESA mounting *	✓
Display resolution *	1920 x 1080 pixels	Panel mounting interface	100 x 100 mm
HD type *	Full HD	Cable lock slot *	✓
Native aspect ratio *	16:9	Cable lock slot type	Kensington
Display technology *	LCD	Tilt adjustment	✓
Panel type *	VA	Tilt angle range	-5 - 20°
LED backlight	✓	On Screen Display (OSD)	✓
Backlight type	W-LED		
Touchscreen *	✗		Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
Display brightness (typical)	250 cd/m²	On Screen Display (OSD) languages	
Response time *	4 ms		
Response time (MPRT)	1 ms		
Anti-glare screen	✓		
Screen shape *	Flat	Plug and Play	✓
Contrast ratio (typical) *	4000:1	LED indicators	Operation, Stand-by
Dynamic contrast ratio marketing name	Mega Infinity DCR		
Maximum refresh rate *	100 Hz	Power	
Viewing angle, horizontal	178°	Energy efficiency class (SDR) *	Not available
Viewing angle, vertical	178°	Energy efficiency class (HDR) *	Not available
Display number of colours *	16.7 million colours	Power consumption (typical) *	32.89 W
Pixel pitch	0.3114 x 0.3114 mm	Power consumption (standby) *	0.5 W
Pixel density	82 ppi	Power consumption (off)	0.3 W
Horizontal scan range	30 - 115 kHz	AC input voltage	100 - 240 V
Vertical scan range	48 - 100 Hz	AC input frequency	50/60 Hz
Viewable size, horizontal	59.8 cm	Power supply type	Internal
Viewable size, vertical	33.6 cm		
Display diagonal (metric)	68.6 cm	Operational conditions	
DDC/CI	✓	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-20 - 60 °C
		Operating relative humidity (H-H)	20 - 80%

Display		Operational conditions	
Haze rate	25%	Operating altitude	0 - 3658 m
Surface hardness	3H	Non-operating altitude	0 - 12192 m
Colour depth	8 bit	Weight & dimensions	
Colour gamut standard	sRGB	Width (with stand)	614 mm
Display sRGB	✓	Depth (with stand)	231 mm
Display panel size	27 inch/68.6 cm	Height (with stand)	457 mm
Performance		Weight (with stand)	3.74 kg
NVIDIA G-SYNC *	✗	Width (without stand)	614 mm
AMD FreeSync *	✗	Depth (without stand)	53 mm
VESA Adaptive Sync support	✓	Height (without stand)	367 mm
Component video sync	Separate Sync, Sync-on-green (SOG)	Weight (without stand)	3.28 kg
Flicker-free technology	✓	Packaging data	
Low Blue Light technology	✓	Package width	730 mm
Multimedia		Package depth	123 mm
Number of speakers	2	Package height	446 mm
RMS rated power	4 W	Package weight	5.35 kg
Built-in speaker(s) *	✓	Packaging content	
Built-in camera *	✗	Stand included	✓
Design		Manual	✓
Market positioning *	Home	Sustainability	
Product colour *	Black	Doesn't contain	Mercury, PVC/BFR
Ports & interfaces		Other features	
Built-in USB hub *	✗	Compatible operating systems	Mac OS X; Windows 11/10/8.1/8
VGA (D-Sub) ports quantity	1	Exterior finish type	Textured
HDMI *	✓	Monitor sync input signal	Separate Sync; Sync on Green
HDMI ports quantity	1	User controls	Power On/Off; Menu/OK; Input/Down; SmartImage/Back; Volume
HDMI version	1.4	Picture enhancement	SmartImage
Audio output	✓	Signal input	HDMI (digital, HDCP); VGA (Analogue)
PC Audio in	✓	Regulatory Approvals	CB; CE Mark; CCC; CECP; CEL; ICES-003; BSMI; EAC; FCC; PSB; TUV Ergo; TUV/GS
HDCP	✓	EasyRead mode	✓
HDCP version	1.4	LowBlue mode	✓
		Mean time between failures (MTBF)	30000 h
		Recycling data	
		Packaging recyclability rate	100%



8712581804374

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.