

ZYXEL

Zyxel GS1005HP Unmanaged Gigabit Ethernet (10/100/1000)  
Power over Ethernet (PoE) Silver

Brand : Zyxel

Product code: GS1005HP-EU0101F

Product name : GS1005HP

- Compatible With IEEE 802.3af and 802.at Compliant PDs
- Auto-MDI/MDIX in all ports
- IEEE802.3x Flow Control
- IEEE 802.1p QoS
- Jumbo frame support up to 9 KB

GS1005HP 5-Port GbE Unmanaged PoE Switch

Zyxel GS1005HP. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex. MAC address table: 2048 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE)



| Management features                             |                                                                  | Power over Ethernet (PoE)                      |                    |
|-------------------------------------------------|------------------------------------------------------------------|------------------------------------------------|--------------------|
| Switch type *                                   | Unmanaged                                                        | Power over Ethernet plus (PoE+) ports quantity | 4                  |
| Quality of Service (QoS) support                | ✓                                                                | Power over Ethernet (PoE) power per port       | 30 W               |
| Ports & interfaces                              |                                                                  | Total Power over Ethernet (PoE) budget         | 60 W               |
| Basic switching RJ-45 Ethernet ports quantity * | 5                                                                | Operational conditions                         |                    |
| Basic switching RJ-45 Ethernet ports type *     | Gigabit Ethernet (10/100/1000)                                   | Operating temperature (T-T)                    | 0 - 40 °C          |
| Network                                         |                                                                  | Storage temperature (T-T)                      | -40 - 70 °C        |
| Networking standards *                          | IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | Operating relative humidity (H-H)              | 10 - 90%           |
| 10G support *                                   | ✗                                                                | Storage relative humidity (H-H)                | 10 - 90%           |
| Full duplex                                     | ✓                                                                | Weight & dimensions                            |                    |
| Flow control support                            | ✓                                                                | Width                                          | 121 mm             |
| Auto MDI/MDI-X                                  | ✓                                                                | Depth                                          | 75 mm              |
| Data transmission                               |                                                                  | Height                                         | 26 mm              |
| Switching capacity *                            | 10 Gbit/s                                                        | Weight                                         | 235 g              |
| MAC address table *                             | 2048 entries                                                     | Packaging content                              |                    |
| Jumbo frames support                            | ✓                                                                | Quick start guide                              | ✓                  |
| Jumbo frames                                    | 9126                                                             | Packaging data                                 |                    |
| Design                                          |                                                                  | AC adapter included                            | ✓                  |
| Product colour                                  | Silver                                                           | Package width                                  | 210 mm             |
| Performance                                     |                                                                  | Package depth                                  | 132 mm             |
| Buffer size                                     | 128 KB                                                           | Package height                                 | 78 mm              |
| Power                                           |                                                                  | Package weight                                 | 834 g              |
| AC input voltage                                | 100 - 240 V                                                      | Certificates                                   |                    |
| Output voltage                                  | 55 V                                                             | Certification                                  | CE, FCC, BSMI, EAC |
| Output current                                  | 1.3 A                                                            | Logistics data                                 |                    |
| Power over Ethernet (PoE)                       |                                                                  | Harmonized System (HS) code                    | 85176990           |
| Power over Ethernet (PoE) *                     | ✓                                                                |                                                |                    |



4718937603923

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.