



APC BV1000I-GR источник бесперебойного питания
Интерактивная 1 kVA 600 W 4 розетка(и)

Производитель : APC

Код товара: BV1000I-GR


Модель : BV1000I-GR



APC BV1000I-GR. топология ИБП: Интерактивная, Выходная мощность: 1 kVA, Выходная мощность: 600 W. Типы розеток: Тип F, Количество розеток: 4 розетка(и). Технология батареи: Герметичная свинцово-кислотная (VRLA), Емкость батареи: 9 Ah, Напряжение батареи: 12 V. Формат: Компактный, Цвет товара: Черный, Длина кабеля: 1,52 m. Compliance certificates: RoHS, Сертификация: CE REACH



Свойства		Дизайн	
топология ИБП *	Интерактивная	Длина кабеля	1,52 m
Выходная мощность *	1 kVA	Цвет товара *	Черный
Выходная мощность *	600 W	Светодиодные индикаторы	✓
Форма волны *	Синусоидальная	International Protection (IP) код	IP20
Входное напряжение (мин) *	170 V	Условия эксплуатации	
Входное напряжение (макс) *	280 V	Диапазон температур при эксплуатации	0 - 40 °C
Частота входного сигнала *	50/60 Hz	Диапазон относительной влажности при эксплуатации	0 - 90%
Частота выходного сигнала	50/60 Hz	Рабочая высота	0 - 2032,1 m
Автоматическая регулировка напряжения (AVR)	✓	Сертификаты	
Значение потока энергии	156 J	Compliance certificates	RoHS
Время перехода (режим линии в режим батареи)	6 ms	Сертификация	CE REACH
Количество фаз на входе	1	Содержимое упаковки	
Количество фаз на выходе	1	Карта управления в комплекте	✗
Уровень шума	40 dB	Вес и размеры	
Защита от перенапряжения	✓	Ширина	160,5 mm
Звуковые сигналы	✓	Глубина	305 mm
Режимы звукового сигнала	Сигнализация при включении батареи, Сигнализация при низком заряде батареи, Сигнализация при перегрузке	Высота	92,5 mm
		Вес	5,7 kg
		Данные об упаковке	
Порты и интерфейсы		Ширина упаковки	373 mm
Типы розеток	Тип F	Глубина упаковки	143 mm
Количество розеток	4 розетка(и)	Высота упаковки	237 mm
Слот расширения SmartSlot	✗	Масса брутто	6 kg
SmartConnect port	✗	Логистические данные	
Батарея		Код гармонизированной системы описания (HS)	85078000
Технология батареи	Герметичная свинцово-кислотная (VRLA)	Гарантийный срок	2 лет
Емкость батареи	9 Ah	Прочие свойства	
Напряжение батареи	12 V	Номинальное выходное напряжение	230 V
Время подзарядки батареи	8 h		
Холодный запуск	✓		
Дизайн			
Формат *	Компактный		



0731304338246



731304338246

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.