Lindy 1m High Speed HDMI Cable, Anthra Line

Brand : Lindy

Product code: 36962

Product name : 1m High Speed HDMI Cable, Anthra Line

1m High Speed HDMI Cable, Anthra Line

Lindy 1m High Speed HDMI Cable, Anthra Line:

From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 30AWG copper conductors with for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

The HDMI 2.0 specification is supported for 18Gbps bandwidth capacity in cable lengths up to 5m.

Anthra Line HDMI cables are available in lengths from 0.3m to 5m.

Features	
Cable length *	1 m
Connector 1 *	HDMI Type A (Standard)
Connector 2 *	HDMI Type A (Standard)
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Product colour *	Black, Grey
HDMI version	2.0
Supported graphics resolutions	4096 x 2160
Supported video modes	2160p
HDMI Ethernet channel	✔
Data transfer rate	18 Gbit/s
Maximum resolution	4096 x 2160 pixels
AWG wire size	30
Contact material	Phosphor copper
Connector contacts plating *	Gold
Connector housing material	Polyvinyl chloride (PVC)
Connector material	Gold
Cable material	Copper
Cable type	Round cable
Cable jacket material	Polyvinyl chloride (PVC)

Features	
Shield material	Copper
Bend radius (min)	4.8 cm
Colour depth	8 bit
Plug and Play	✔
Colour sampling	4:4:4
Nominal attenuation	300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB, 2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB
Operational conditions	
Operating temperature (T-T)	-10 - 80 °C
Storage temperature (T-T)	-10 - 80 °C
Certificates	
Certification	RoHS, REACH, UL, ATC
Weight & dimensions	
Cable diameter	6 mm
Connector 1 dimensions (WxDxH)	20 x 34.2 x 10.9 mm
Connector 2 dimensions (WxDxH)	20 x 34.2 x 10.9 mm
Packaging data	
Package type	Polybag
Quantity per pack *	1 pc(s)
Logistics data	
Harmonized System (HS) code	84733080

4002888369626

Catalog Object Cloud

Publication date: 09-SEP-2026. Prints or copies of Information are only valid on the printed Publication date