Lindy 3m USB 2.0 Type A Extension Cable, Anthra Line

Brand : Lindy

Product code: 36704

Product name : 3m USB 2.0 Type A Extension Cable, Anthra Line

3m USB 2.0 Type A Extension Cable, Anthra Line

Lindy 3m USB 2.0 Type A Extension Cable, Anthra Line:

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type A Extension cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and nickel connectors maintain optimal signal integrity and maximum reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Anthra Line USB 2.0 Type A Extension cables are available in lengths from 0.2m to 5m.
Lindy 3m USB 2.0 Type A Extension Cable, Anthra Line. Cable length: 3 m. Connector 1: USB A, Connector 2: USB A, USB version: USB 2.0, Maximum data transfer rate: 0.48 Gbit/s, Connector contacts plating: Gold, Product colour: Black, Grey, Magnetically shielded

Features	
USB version *	USB 2.0
Connector 1 *	USB A
Connector 2 *	USB A
Connector 1 gender *	Male
Connector 2 gender *	Female
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	26/28
Connector material	Nickel
Contact material	Copper
Connector contacts plating	Gold
Magnetically shielded	✔
Cable jacket material	Polyvinyl chloride (PVC)
Conductor material	Tinned copper
Connector shielding	✔
Connector shield material	Aluminium
Connector housing material	Polyvinyl chloride (PVC)
Maximum data transfer rate	480 Mbit/s
Maximum data transfer rate	0.48 Gbit/s
Cable type	Round cable

Features	
Product colour *	Black, Grey
Nominal attenuation	5.8db/km
Weight & dimensions	
Cable length *	3 m
Cable diameter	4.4 mm
Bend radius (min)	1.6 cm
Connector 1 dimensions (WxDxH)	15.5 x 35 x 7.8 mm
Connector 2 dimensions (WxDxH)	17 x 35 x 9.8 mm
Packaging data	
Package type	Polybag
Packaging content	
Quantity per pack *	1 pc(s)
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	0 - 60 °C
Certificates	
Certification	RoHS, REACH, UL
Logistics data	
Harmonized System (HS) code	84733080

4002888367042

Catalog Object Cloud

Publication date: 09-SEP-2026. Prints or copies of Information are only valid on the printed Publication date