



TP-Link Archer C54 wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) Black

Brand : TP-Link

Product code: ARCHER C54

Product name : Archer C54

- Faster AC Wi-Fi—AC1200 dual-band is ideal for 4K video streaming and high-speed downloading
 - Far-Reaching Coverage—4x antennas and Beamforming delivers extensive Wi-Fi coverage and reliable connections
 - Multi-Mode 3-in-1—Supports Router, Access Point, and Range Extender modes for added flexibility
 - Parental Controls—Manages when and how connected devices can access the internet
 - Guest Network—Provides separate access for guests in order to secure the host network
 - Smooth HD Streaming—Supports IGMP Proxy/Snooping, Bridge, and Tag VLAN to optimize IPTV streaming
 - IPv6 Supported—Compatible with the IPv6 (the latest Internet Protocol version 6)
 - Compact and Mountable—Designed to conserve space and complement any décor
- Dual-band, IEEE 802.11ac/n/a, 5 GHz: 867 Mbps, MU-MIMO



WAN connection		Security	
Ethernet WAN *	✓	Security algorithms	WEP, WPA, WPA2, WPA2-Enterprise
DSL WAN *	✓	Firewall	✓
SIM card slot *	✗	Access Control List (ACL)	✓
Wireless LAN features		Stateful Packet Inspection (SPI)	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	DMZ support	✓
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Protocols	
WLAN data transfer rate (max) *	867 Mbit/s	DHCP client	✓
WLAN data transfer rate (first band)	867 Mbit/s	DHCP server	✓
WLAN data transfer rate (second band)	300 Mbit/s	Universal Plug and Play (UPnP)	✓
Network		Design	
Ethernet LAN *	✓	Product colour	Black
Ethernet LAN interface type *	Fast Ethernet	Product type *	Tabletop router
Ethernet LAN data rates	10,100 Mbit/s	Antenna	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11d, IEEE 802.11g, IEEE 802.11n	Antenna design *	External
Port forwarding	✓	Antennas quantity	4
Port triggering	✓	Power	
Dynamic DNS (DDNS)	✓	Power source type *	AC
Mobile network		Output voltage	9 V
3G	✗	Output current	0.85 A
4G	✗	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
Ethernet LAN (RJ-45) ports *	4	Storage temperature (T-T)	-40 - 60 °C
		Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%

Management features		Weight & dimensions	
Quality of Service (QoS) support	✓	Width	115 mm
Reset button	✓	Depth	106.7 mm
WPS push button	✓	Height	24.3 mm
MU-MIMO technology	✓		



6935364089337

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.