



Dahua Technology XVR5104HS-4KL-I3 Melns

Zīmols : Dahua Technology

Preces kods: DH-XVR5104HS-4KL-I3

Modeļa nosaukums : XVR5104HS-4KL-I3

Dahua Technology XVR5104HS-4KL-I3. Produkta krāsa: Melns, Maksimālais video izšķirtspēju: 3840 x 2160 pikseli, Video kompresijas formāti: H.264, H.264+, H.265, H.265+. Video ievades kanāli: 4 kanāli, Audio izeja: 1 RCA. Ethernet interfeisa tips: Ātrais Ethernet, Atbalstāmie tīkla protokoli: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P. Cietā diska interfeiss: SATA, Maksimālā cietā diska ietilpība: 16 TB. Barošanas avota tips: Līdzstrāvas, Līdzstrāvas spriegums: 12 V, Enerģija patēriņš: 7 W



Darbības rādītāji	
Maksimālais video izšķirtspēju	3840 x 2160 pikseļi
Video kompresijas formāti	H.264, H.264+, H.265, H.265+
Atbalstītie audio formāti	G.711 A-law, G.711 μ-law, PCM
Backup funkcija	✓
Video tveršanas ātrums	30 fps
Video tveršanas ātrums (PAL)	25 fps
Video tveršanas ātrums (NTSC)	30 fps
Video zudumu noteikšana	✓
Video kustības uztveršana	✓
Kanālu skaits	4 kanāli
Produkta krāsa *	Melns
Nodrošināta operētājsistēma	Integrētais LINUX
PTZ kontrole	✓
Statņa kapacitāte	1U
Sertifikācija	FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024
Savienojamība	
Video ievades kanāli *	4 kanāli
BNC ieejas porti	4
HDMI pieslēgvietu skaits	1
Audio ieeja	1
Audio izeja	1 RCA
USB 2.0 pieslēgvietu skaits	2
RS-485 porti	1
Tīklošana	
Ethernet/LAN savienojums	✓

Tīklošana	
Ethernet LAN (RJ-45) pieslēgvietu skaits	1
Atbalstāmie tīkla protokoli	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Diskdzinis	
Atbalstāmo cieto disku skaits	1
Cietā diska interfeiss	SATA
Maksimālā cietā diska ietilpība	16 TB
Enerģijas pārvaldība	
Barošanas avota tips	Līdzstrāvas
Līdzstrāvas spriegums	12 V
Enerģija patēriņš	7 W
Svars&dimensijas	
Platums	260 mm
Dziļums	237,9 mm
Augstums	47,6 mm
Svars	530 g
Informācija par iepakojumu	
Iepakojuma platums	333 mm
Iepakojuma dziļums	315 mm
Iepakojuma augstums	89 mm
Iepakojuma svars	1,07 kg
Displejs	
Iebūvēta displeja	✗

Tīklošana		Ārējās vides apstākļi	
Ethernet interfeisa tips	Ātrais Ethernet	Darbības temperatūras amplitūda (T-T)	-10 - 55 °C
		Darbības relatīvā mitruma amplitūda	10 - 90%



6939554930430

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.