

Epson PowerLite EB-815E

Brand : Epson Product family: PowerLite Product code: V11HA99180

Product name : EB-815E

- Scalable 4KE display for any room: 80-160" UST display for unrestricted viewing (no shadows/reflections)
 - Bright and energy efficient laser: 5,000 lumens CLO with 3LCD technology for brighter colours
 - Effortless connectivity options: Auto-on, wired/wireless display with USB 2A output for smart sticks
 - Simple to use and built to last: Virtually maintenance free with 5-year, 12,000hr warranty
 - LED/Video wall alternative: Surprisingly affordable with low energy consumption
- Super UST 4KE laser display

GARAN

EPSON

5

365



EB-815E

БГ

Гаранция от производителя в години | CS Záruka výrobce v letech | DA Producentgarantiens varighed i år | DE Herstellergarantie in Jahren | EL Εγγύηση προμηθευτού σε έτη | EN Producer guarantee in years | ES Garantía del productor en años | ET Tootja garanti aastades | FI Tuottajan takuu vuosina | FR Garantie du producteur en années | GA Fáilteacht an tairéara de réir blianta | HR Jamstvo proizvođača u godinama | HU Gyártói jótállás években | IT Garanzia del produttore in anni | LT Gamintojo garantija metais | LV Ražotāja garantija gados | MT Garanzija tal-produttur fi snin | NL Producentgarantie in jaren | PL Ochrona producenta w latach | PT Garantia do produtor em anos | RO Garanția producătorului în ani | SK Záruka výrobcu v rokoch | SL Garancija proizvajalca v letih | SV Tillverkarens garanti i antal år



Projector		Design	
Smart projector *	✗	Cable lock slot type	Kensington
Screen size compatibility *	2032 - 4064 mm (80 - 160")	Display	
Contrast ratio (dynamic)	5000000:1	Built-in display *	✗
Projector brightness *	5000 ANSI lumens	Power	
Projection technology *	3LCD	Power source *	AC
Projector native resolution *	1080p (1920x1080)	Power consumption (typical) *	290 W
Contrast ratio (typical) *	2500000:1	Power consumption (max)	380 W
Native aspect ratio *	16:9	Power consumption (economy mode)	192 W
Projector brightness (economic mode)	3500 ANSI lumens	AC input voltage	100 - 240 V
Vertical scan range	192 - 240 Hz	AC input frequency	50 - 60 Hz
Matrix size	1.57 cm (0.62")	AC adapter output voltage	100 - 240 V
Heat dissipation	1292 BTU/h	Operational conditions	
Light source		Storage temperature (T-T)	-10 - 60 °C
Light source type *	Laser	Operating relative humidity (H-H)	20 - 80%
Service life of light source *	20000 h	Storage relative humidity (H-H)	10 - 90%
Service life of light source (economic mode)	30000 h	Weight & dimensions	
Lens system		Width	695 mm
Focus *	Manual	Depth	341 mm
Focal length range	2.3 mm	Height	156 mm
Fixed focal length	2.3 mm	Weight *	12.5 kg
F-number (relative aperture)	1.8	Package width	460 mm
Zoom capability	✓	Package depth	790 mm
Zoom ratio	1.35:1	Package height	310 mm
Throw ratio	0.16 - 0.22:1	Package weight	16.9 kg
Video		Packaging content	
Analog signal format system *	Not supported	Remote control included *	✓
Full HD *	✓	Batteries included	✓
3D *	✗		
Video processing	10 bit		

Video		Packaging content	
Colour modes (2D)	Cinema, Dynamic, Natural	Bundled software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager, Epson Projector Management, Epson Setting Assistant
Video colour modes	Blackboard, Cinema, DICOM simulation mode, Dynamic, Multi-projection, Natural, Presentation		
Ports & interfaces		Technical details	
Service port type	USB Type-B	Other features	21:9 aspect ratio support, 4K enhancement, A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Email notification, Fit to Screen, Home Screen, Horizontal and vertical keystone correction, Image Shift, JPEG Viewer, Long light source life, PC Free, Point correction, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Source function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App
USB 2.0 ports quantity	2		
Serial interface type *	RS-232C		
HDMI ports quantity *	3		
DVI port *	✗		
Network			
Smart TV *	✗		
Ethernet LAN *	✓		
Ethernet LAN (RJ-45) ports	1		
Ethernet LAN data rates	10,100 Mbit/s		
Wi-Fi *	✓		
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)		
Miracast	✓		
Storage		Mobile app support	✓
Card reader integrated *	✗	Power consumption	290 Watt (Normal On-Mode), 192 Watt (Eco On-Mode), 380 Watt (Normal Peak-mode), 286 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby)
Features			
Interactive *	✗	Logistics data	Quantity per pack 1 pc(s) Products per pallet 12 pc(s) Pallet gross length 120 cm Pallet gross width 80 cm Pallet gross height 2.01 m Products per pallet layer 2 pc(s) Products per pallet layer (UK) 2 pc(s) Products per pallet (UK) 12 pc(s) Pallet length (UK) 120 cm Pallet height (UK) 2.01 m
Noise level (economic mode)	26 dB		
Noise level *	35 dB		
Country of origin	Philippines		
High Dynamic Range (HDR) supported	✓		
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)	Other features	Air filter, Ceiling mount, Connection and control box, MB22 ceiling mount, Safety wire set, Visualiser camera, WP System - ELPWP10, WP System - ELPWP20, Wall hanging bracket, Wall mount, Wireless LAN unit, Wireless transmitter - ELPWT01 USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, HDMI in (2x), HDMI out, HDBaseT, Miracast 0.62 inch with C2 Fine HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink Power cable, Quick Start Guide, Remote control incl. batteries, Warranty Documents Kensington lock, Control panel lock, Password lock, Padlock, Wireless LAN unit lock, Wireless LAN security, Password protection
Password protection	✓		
Multimedia			
Built-in speaker(s) *	✗		
Design			
Market positioning *	Business		
Product type *	Ultra short throw projector		
Product colour *	Black		
Placement	Ceiling, Desktop, TV cabinet, Wall		
Cable lock slot	✓		
		Option type	
		Interface	
		Control panel	
		Supported network protocols	
		Box contents	
		Security features	



8715946726540

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.