



Cudy FS1026PS1 tīkla pārslēgs Nepārvaldīts Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Melns

Zīmols : Cudy

Preces kods: FS1026PS1

Modeļa nosaukums : FS1026PS1

Cudy FS1026PS1. Slēdža tips: Nepārvaldīts. Basic switching RJ-45 Ethernet portu veids: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet portu daudzums: 24. Adrešu tabulas izmērs: 2048 ieraksti, Komutācijas ietilpība: 10,8 Gbit/s. Tīkla standarts: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. DC ievades spriegums: 48 - 55 V. Saspraudnis: AC barošanas spraudnis. Power over Ethernet (PoE). Statņa montāža



Vadības īpašības		Energijas pārvaldība	
Slēdža tips *	Nepārvaldīts	Jaudas avots *	AC
Savienojamība		Strāvas barošana iekļauta *	✓
Basic switching RJ-45 Ethernet portu daudzums *	24	Mainstrāvas ievades spriegums	100 - 240 V
Basic switching RJ-45 Ethernet portu veids *	Gigabit Ethernet (10/100/1000)	Mainstrāvas ievades frekvence	50 - 60 Hz
Gigabit Ethernet (copper) pieslēgvietu skaits	2	DC ievades spriegums	48 - 55 V
SFP moduļa slotu skaits	1	Power over Ethernet (PoE)	
Saspraudnis	AC barošanas spraudnis	Power over Ethernet (PoE) *	✓
Tīklošana		Power over Ethernet (PoE) jauda uz pieslēgvietu	30 W
Tīkla standarts *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Kopējais Power over Ethernet (PoE) budžets	300 W
10G atbalsta *	✗	Ārējās vides apstākļi	
Vara Ethernet kabeļu tehnoloģija	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X	Darbības temperatūras amplitūda (T-T)	0 - 40 °C
Kabeļu tipi, kas ir atbalstīti	Cat5, Cat3, Cat5e	Uzglabāšanas temperatūras amplitūda (T-T)	-40 - 70 °C
Atbalsta VLAN	✓	Darbības relatīvā mitruma amplitūda	10 - 90%
Datu pārraide		Uzglabāšanas relatīvā mitruma amplitūda	10 - 95%
Komutācijas ietilpība *	10,8 Gbit/s	Ekspluatācijas augstums	0 - 3000 m
Pakešu apstrādes jauda	8 miljons pakešu sekundē	Svars&dimensijas	
Adrešu tabulas izmērs *	2048 ieraksti	Platums	180 mm
Pakešu buferatmiņa	0,375 MB	Dziļums	440 mm
Dizains		Augstums	44 mm
Statņa montāža *	✓	Informācija par iepakojumu	
Sakraujams *	✓	Iepakojuma platums	487 mm
Produkta krāsa	Melns	Iepakojuma dziļums	267 mm
LED indikatori	✓	Iepakojuma augstums	84 mm
Darbības rādītāji			
Vidējais laiks starp kļūmēm (MTBF)	100000 h		



6971690791353

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.