



## LG 49VL5PJ-A Signage Display Panorama design 124.5 cm (49") 500 cd/m<sup>2</sup> Full HD Black 24/7



**Brand :** LG

**Product code:** 49VL5PJ-A

**Product name :** 49VL5PJ-A

- Brightness(Typ.) : 500 nit
  - Bezel : 2.25 mm (T/L), 1.25 mm (B/R)
  - Depth : 89.7 mm
  - Interface : HDMI/ DP/ DVI-D/ USB/ RS232C/ RJ45/ Audio/ IR
- 49", 500 nits, 1920 x 1080 px, FHD, IPS, 100-240V, 50/60Hz, 1077.6 x 607.8 x 89.7 mm, 17.8 kg

LG 49VL5PJ-A Signage Display Panorama design 124.5 cm (49") 500 cd/m<sup>2</sup> Full HD Black 24/7:

### Daisy Chain Capability

By using this daisy-chained network feature, you can execute commands such as controlling, monitoring and even updating firmware.

### Real-Time LG ConnectedCare

Maintenance is easy and fast with the optional LG ConnectedCare\* service, a cloud service solution provided by LG. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, enabling the stable operation of clients' businesses.

LG 49VL5PJ-A. Product design: Panorama design. Display diagonal: 124.5 cm (49"), Display resolution: 1920 x 1080 pixels, Display brightness: 500 cd/m<sup>2</sup>, HD type: Full HD. Operating hours (hours/days): 24/7. Product colour: Black

| Display                       |                       | Design                                  |                                 |
|-------------------------------|-----------------------|-----------------------------------------|---------------------------------|
| Panel type                    | IPS                   | Bezel width (top)                       | 2.25 mm                         |
| LED backlighting type         | Direct-LED            | <b>Performance</b>                      |                                 |
| Display diagonal *            | 124.5 cm (49")        | Purpose *                               | Commercial                      |
| Display resolution *          | 1920 x 1080 pixels    | On Screen Display (OSD)                 | ✓                               |
| Display brightness *          | 500 cd/m <sup>2</sup> | Operating hours (hours/days)            | 24/7                            |
| HD type *                     | Full HD               | <b>Power</b>                            |                                 |
| Touchscreen *                 | ✗                     | Power consumption (typical) *           | 110 W                           |
| Native aspect ratio           | 16:9                  | Power consumption (off)                 | 0.5 W                           |
| Response time                 | 8 ms                  | Energy efficiency class (SDR)           | G                               |
| Contrast ratio (typical)      | 1000:1                | Energy consumption (SDR) per 1000 hours | 73 kWh                          |
| Contrast ratio (dynamic)      | 500000:1              | AC input voltage                        | 100-240 V                       |
| Viewing angle, horizontal     | 178°                  | AC input frequency                      | 50 - 60 Hz                      |
| Viewing angle, vertical       | 178°                  | Heat dissipation                        | 375 BTU/h                       |
| Display number of colours     | 1.07 billion colours  | Energy efficiency scale                 | A to G                          |
| Rated lifetime                | 60000 h               | <b>Weight &amp; dimensions</b>          |                                 |
| Native refresh rate           | 60 Hz                 | Display width                           | 1077.6 mm                       |
| Haze rate                     | 3%                    | Display depth                           | 89.7 mm                         |
| <b>Ports &amp; interfaces</b> |                       | Display height                          | 607.8 mm                        |
| HDMI ports quantity *         | 2                     | Display weight                          | 17.8 kg                         |
| HDMI version                  | 2.2                   | <b>Packaging data</b>                   |                                 |
| DVI port *                    | ✓                     | Package width                           | 1198 mm                         |
| DVI-D ports quantity          | 1                     | Package depth                           | 247 mm                          |
| DisplayPorts quantity *       | 1                     | Package height                          | 756 mm                          |
| USB port *                    | ✓                     | Package weight                          | 21.9 kg                         |
| USB ports quantity            | 1                     | <b>Packaging content</b>                |                                 |
| USB version                   | 2.0                   | Remote control included                 | ✓                               |
| Ethernet LAN (RJ-45) ports    | 1                     | Cables included                         | DisplayPort, LAN (RJ-45), Power |
| RS-232C                       | ✓                     |                                         |                                 |
| <b>Design</b>                 |                       |                                         |                                 |
| Product design *              | Panorama design       |                                         |                                 |
| Product colour *              | Black                 |                                         |                                 |

| Design                   |              | Operational conditions            |           |
|--------------------------|--------------|-----------------------------------|-----------|
| Screen shape             | Flat         | Operating temperature (T-T)       | 0 - 40 °C |
| VESA mounting *          | ✓            | Operating relative humidity (H-H) | 10 - 80%  |
| Panel mounting interface | 600 x 400 mm | Network                           |           |
| Bezel width (bottom)     | 2.25 mm      | Ethernet LAN *                    | ✓         |
| Bezel width (side)       | 1.25 mm      | Wi-Fi *                           | ✗         |



8806091383150



8806091370211



0195174013922



195174013922

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.