



## Lindy DST-Mini XT 810, USB-C Laptop Mini Docking Station with Single Display (8K) or Dual Display (4K60) and 100W Pass-Through Charging

**Brand :** Lindy

**Product code:** 43392

**Product name :** DST-Mini XT 810, USB-C Laptop Mini Docking Station with Single Display (8K) or Dual Display (4K60) and 100W Pass-Through Charging

- Connects an HDMI and/or a DisplayPort display, USB peripherals and power over a single cable
- Supports 8K 30Hz for a single display or 4K 60Hz for two displays (MST)\*
- Integrated 3 port USB SuperSpeed 10Gbps Hub (2 x Type A, 1 x Type C)
- USB Power Delivery capable up to 100W
- 2 year warranty

DST-Mini XT 810, USB-C Laptop Mini Docking Station with Single Display (8K) or Dual Display (4K60) and 100W Pass-Through Charging

Lindy DST-Mini XT 810, USB-C Laptop Mini Docking Station with Single Display (8K) or Dual Display (4K60) and 100W Pass-Through Charging. Connectivity technology: Docking, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Anthracite, Compatible memory cards: MicroSD (TransFlash), SD, Data transfer rate: 10 Gbit/s. Power source type: USB, Power connector: USB Type-C, Power supply: 15 W. Width: 270 mm, Depth: 45 mm, Height: 16 mm



| Ports & interfaces                              |                                  | Performance                       |                             |
|-------------------------------------------------|----------------------------------|-----------------------------------|-----------------------------|
| Connectivity technology *                       | Docking                          | Product colour *                  | Anthracite                  |
| Host interface *                                | USB 3.2 Gen 1 (3.1 Gen 1) Type-C | Plug and Play                     | ✓                           |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 2                                | Housing material                  | Aluminium                   |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 2                                | Certification                     | CE, FCC, REACH & RoHS, CP65 |
| USB Power Delivery (USB PD)                     | ✓                                | Power                             |                             |
| USB Power Delivery revision                     | 3.0                              | Power source type                 | USB                         |
| USB Power Delivery up to                        | 100 W                            | Power connector                   | USB Type-C                  |
| HDMI ports quantity *                           | 1                                | Power supply                      | 15 W                        |
| HDMI version                                    | 2.1                              | USB cable length                  | 0.36 m                      |
| DisplayPorts quantity                           | 1                                | Operational conditions            |                             |
| DisplayPort version                             | 1.4a                             | Operating temperature (T-T)       | 0 - 40 °C                   |
| Combo headphone/mic port                        | ✓                                | Storage temperature (T-T)         | -10 - 70 °C                 |
| Headphone outputs *                             | 1                                | Operating relative humidity (H-H) | 0 - 85%                     |
| Headphone connectivity                          | 3.5 mm                           | Sustainability                    |                             |
| HDCP                                            | ✓                                | Sustainability compliance         | ✓                           |
| HDCP version                                    | 1.4/2.2                          | Weight & dimensions               |                             |
| USB Type-C DisplayPort Alternate Mode           | ✓                                | Width                             | 270 mm                      |
| Network                                         |                                  | Depth                             | 45 mm                       |
| Ethernet LAN *                                  | ✓                                | Height                            | 16 mm                       |
| Ethernet LAN (RJ-45) ports                      | 1                                | Weight                            | 224 g                       |
| Ethernet LAN data rates                         | 10,100,1000 Mbit/s               | Packaging data                    |                             |
| Wake-on-LAN ready                               | ✓                                | Quantity per pack                 | 1 pc(s)                     |
| Performance                                     |                                  | Package width                     | 365 mm                      |
| Card reader integrated *                        | ✓                                | Package depth                     | 93 mm                       |
| Compatible memory cards                         | MicroSD (TransFlash), SD         | Package height                    | 35 mm                       |
|                                                 |                                  | Package weight                    | 330 g                       |

| Performance                  |                    | Packaging content       |                                                          |
|------------------------------|--------------------|-------------------------|----------------------------------------------------------|
| Data transfer rate           | 10 Gbit/s          | Manual                  | ✓                                                        |
| Maximum digital resolution   | 7680 x 4320 pixels | Technical details       |                                                          |
| Number of displays supported | 2                  | Warranty period         | 2 year(s)                                                |
| Maximum refresh rate         | 120 Hz             | Compliance certificates | CE, Federal Communications Commission (FCC), REACH, RoHS |



4002888433921

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.