

Epson CO-W01

Brand : Epson

Product code: V11HA86040

Product name : CO-W01

- Create the big screen experience: From box sets to business presentations, capture everyone's attention
 - Bright even with ambient light: Equally high White and Colour Light Output of 3,000 lumens
 - Affordable, high-tech equipment: Enjoy this WXGA projector
 - Long-lasting solution: 18 years' worth of entertainment2
 - Portable and quick to set up: Easy set up with keystone slider for perfect alignment
- WXGA projector

Epson CO-W01. Projector brightness: 3000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WXGA (1200x800). Light source type: Lamp, Service life of light source: 6000 h, Service life of light source (economic mode): 12000 h. Focus: Manual, Zoom ratio: 1.35:1, Throw ratio: 1.27 - 1.71:1. Video processing: 8 bit, Colour modes (2D): Cinema, Dynamic, Video colour modes: Blackboard, Cinema, Dynamic, Presentation. Noise level: 38 dB, Noise level (economic mode): 29 dB, Country of origin: Philippines

CO-W01



CO-W01



Projector		Design	
Screen size compatibility *	838.2 - 9601.2 mm (33 - 378")	Market positioning *	Presentation
Projection distance	0.9 - 10.4 m	Product colour *	White
Projection distance (wide)	0.9 - 10.4 m	Placement	Ceiling, Desktop
Projection distance (tele)	0.9 - 10.4 m	Cable lock slot	✔
Projector brightness *	3000 ANSI lumens	Cable lock slot type	Kensington
Projection technology *	3LCD	Power	
Projector native resolution *	WXGA (1200x800)	Power source *	AC
Native aspect ratio *	16:10	Power consumption (typical) *	270 W
Number of colours	16.7 million colours	Power consumption (standby) *	0.5 W
Projector brightness (economic mode)	2000 ANSI lumens	Power consumption (economy mode)	214 W
Vertical scan range	100 - 120 Hz	AC input voltage	100 - 240 V
Keystone correction, horizontal	±30°	AC input frequency	50 - 60 Hz
Keystone correction, vertical	±30°	Operational conditions	
Matrix size	1.5 cm (0.59")	Operating temperature (T-T)	5 - 40 °C
Vertical synchronization (min)	100 kHz	Storage temperature (T-T)	-10 - 60 °C
Vertical synchronization (max)	120 kHz	Operating relative humidity (H-H)	-10 - 60%
Light source		Storage relative humidity (H-H)	10 - 90%
Light source type *	Lamp	Weight & dimensions	
Service life of light source *	6000 h	Width	295 mm
Service life of light source (economic mode)	12000 h	Depth	211 mm
Lamp type	UHE	Height	87 mm
Lamp power	188 W	Weight *	2.4 kg
Lens system		Package width	325 mm
Focus *	Manual	Package depth	365 mm
F-number (relative aperture)	1.44	Package height	170 mm
Zoom capability	✔	Package weight	3.68 kg

Lens system		Packaging content	
Zoom ratio	1.35:1	Remote control included *	✓
Throw ratio	1.27 - 1.71:1	Batteries included	✓
Video		Cables included	AC
Analog signal format system *	Not supported	Technical details	
Full HD *	✗	Other features	A/V mute, Built-in speaker, Horizontal and vertical keystone correction, MHL audio/video interface, Quick Corner
3D *	✗		
Video processing	8 bit	Commodity Classification Automated Tracking System (CCATS)	85286200000
Colour modes (2D)	Cinema, Dynamic	Mobile app support	✗
Video colour modes	Blackboard, Cinema, Dynamic, Presentation	Power consumption	270 Watt (Normal Peak-mode), 214 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby)
Ports & interfaces		Logistics data	
HDMI version	1.4	Quantity per pack	1 pc(s)
USB 2.0 ports quantity	2	Products per pallet	72 pc(s)
USB 2.0 Type-A ports quantity	1	Products per pallet layer	6 pc(s)
USB 2.0 Type-B ports quantity	1	Products per pallet layer (UK)	6 pc(s)
HDMI ports quantity *	1	Products per pallet (UK)	72 pc(s)
Storage		Harmonized System (HS) code	85286200000
Card reader integrated *	✗	Other features	
Features		Interface	HDMI 1.4, USB 2.0-A, USB 2.0 Type B (Service Only)
Noise level (economic mode)	29 dB	Control panel	0.59 inch with MLA (D10)
Noise level *	38 dB	Audio system	Standard
Country of origin	Philippines	Box contents	Main unit, Power cable, Quick Start Guide, Remote control incl. batteries, User manual (CD), Warranty card
Multimedia		Security features	Kensington lock, Padlock, Security cable hole
Built-in speaker(s) *	✓		
RMS rated power	5 W		



8715946706849

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.