



## Dahua Technology SG4020LP tīkla pārslēgs Vadīts L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Mels

**Zīmols :** Dahua Technology

**Preces kods:** SG4020LP

**Modeļa nosaukums :** SG4020LP

Dahua Technology SG4020LP. Slēdža tips: Vadīts, Slēdža līmenis: L2. Basic switching RJ-45 Ethernet portu veids: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet portu daudzums: 2, Instalēto SFP moduļu skaits: 2. Adrešu tabulas izmērs: 8000 ieraksti, Komutācijas ietilpība: 40 Gbit/s. Tīkla standarts: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE.... Power over Ethernet (PoE)

| Vadības īpašības                                |                                                                                                                                       | Energijas pārvaldība                            |                         |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------------|
| Slēdža tips *                                   | Vadīts                                                                                                                                | Strāvas barošana iekļauta *                     | ✓                       |
| Slēdža līmenis                                  | L2                                                                                                                                    | Maiņstrāvas ievades spriegums                   | 100 - 240 V             |
| Tīkla bāzēts menedžments                        | ✓                                                                                                                                     | Maiņstrāvas ievades frekvence                   | 47/63 Hz                |
| Pārvaldība no mākoņpakalpojuma                  | ✓                                                                                                                                     | Ieejas strāva                                   | 4 A                     |
| Savienojamība                                   |                                                                                                                                       | Strāvas patēriņš (maks)                         | 212 W                   |
| Basic switching RJ-45 Ethernet portu daudzums * | 2                                                                                                                                     | Jaudas aizsardzības apraksts                    | Pārspriegums, Pārstrāva |
| Basic switching RJ-45 Ethernet portu veids *    | Gigabit Ethernet (10/100/1000)                                                                                                        | Power over Ethernet (PoE)                       |                         |
| Instalēto SFP moduļu skaits *                   | 2                                                                                                                                     | Power over Ethernet (PoE) *                     | ✓                       |
| Tīklošana                                       |                                                                                                                                       | Power over Ethernet (PoE) pieslēgvietu skaits   | 14                      |
| Tīkla standarts *                               | IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3ad, IEEE 802.3z | Power over Ethernet (PoE) jauda uz pieslēgvietu | 30 W                    |
| Plūsmas kontroles atbalsts                      | ✓                                                                                                                                     | Kopējais Power over Ethernet (PoE) budžets      | 190 W                   |
| Linka sakopošana                                | ✓                                                                                                                                     | Ārējās vides apstākļi                           |                         |
| Apraides vētras kontrole                        | ✓                                                                                                                                     | Darbības temperatūras amplitūda (T-T)           | -10 - 55 °C             |
| Ethernet LAN datu pārsūtīšanas ātrums           | 10,100,1000 Mbit/s                                                                                                                    | Uzglabāšanas temperatūras amplitūda (T-T)       | -40 - 70 °C             |
| Atbalsta VLAN                                   | ✓                                                                                                                                     | Darbības relatīvā mitruma amplitūda             | 5 - 95%                 |
| Virtuālā LAN īpašības                           | Port-based VLAN                                                                                                                       | Uzglabāšanas relatīvā mitruma amplitūda         | 5 - 95%                 |
| VLAN skaits                                     | 32                                                                                                                                    | Svars&dimensijas                                |                         |
| Datu pārraide                                   |                                                                                                                                       | Platums                                         | 440 mm                  |
| Komutācijas ietilpība *                         | 40 Gbit/s                                                                                                                             | Dziļums                                         | 220 mm                  |
| Pakešu apstrādes jauda                          | 29,76 miljons pakešu sekundē                                                                                                          | Augstums                                        | 44 mm                   |
| Adrešu tabulas izmērs *                         | 8000 ieraksti                                                                                                                         | Svars                                           | 2,32 kg                 |
| Jumbo Frames atbalsts                           | ✓                                                                                                                                     | Iepakojuma saturs                               |                         |
| Jumbo rāmji                                     | 15                                                                                                                                    | Pievienoti kabeli                               | Līdzstrāvas             |
| Pakešu buferatmiņa                              | 4 MB                                                                                                                                  | Ātrās startēšanas gids                          | ✓                       |
| Drošība                                         |                                                                                                                                       | Informācija par iepakojumu                      |                         |
| DHCP īpašības                                   | DHCP client                                                                                                                           | Iepakojuma platums                              | 540 mm                  |
| Loop aizsardzība                                | ✓                                                                                                                                     | Iepakojuma dziļums                              | 342 mm                  |
| IP-MAC-Port savienošana                         | ✓                                                                                                                                     | Iepakojuma augstums                             | 90 mm                   |
| Dizains                                         |                                                                                                                                       | Iepakojuma svars                                | 2,97 kg                 |
| Produkta krāsa                                  | Mels                                                                                                                                  | Sertifikāti                                     |                         |
| Apvalka materiāls                               | Metāls                                                                                                                                | Atbilstības sertifikāti                         | CE                      |
| Darbības rādītāji                               |                                                                                                                                       |                                                 |                         |
| Vidējais laiks starp kļūmēm (MTBF)              | 762116 h                                                                                                                              |                                                 |                         |
| Energijas pārvaldība                            |                                                                                                                                       |                                                 |                         |

**Enerģijas pārvaldība**

Jaudas avots \* AC



6939554904592

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.